

FT-330 Series – NSF Certified


- ▶ High Accuracy: $\pm 2\%$ of reading
- ▶ High repeatability: $\pm 0.5\%$ of reading
- ▶ Overmolded electronics with integral cable strain reinforcement
- ▶ Measures flow rates from .2 to 4 GPM
- ▶ Lightweight plastic design for multiple mounting positions

The FT-330 is a highly accurate and repeatable, Hall Effect turbine flow sensor designed for low flow OEM applications. This low cost, NSF Certified, NSF/ANSI/CAN 61 flow sensor is ideal for water or beverage dispensing applications or any application with water based liquids. The 316SS shaft coupled with Delrin® bearings allows for accurate measurements during quick dispensing cycles. The sensor's standard power and output specifications make it easy to retrofit existing controllers.

Specifications

Materials	
Body	Glass Reinforced PPO (Noryl)
Turbine	PA Composite (Nylon)
Axle	316 Stainless Steel
Bearings	Delrin® (Polyoxymethylene, POM)
Inlet/Outlet Ports	3/8" NPT Male
Pressure	
Operating	200 PSIG
Burst	1000 PSIG
Operating Temperature	-4°F to 176°F (-20°C to 80°C)
Viscosity	32 to 81 SSU (1.8 to 16 Centistokes)
Recommended Filtration	< 50 Microns
Input Power	5 to 24 VDC @ 8mA
Output (Hz)	NPN Sinking Open Collector @ 25mA Maximum leakage current 10µA (5k to 30k Pull-Up Resistor Required)
Accuracy	$\pm 2\%$ of reading
Repeatability	$\pm 0.5\%$ of reading
Electrical Connection	3 ft PVC cable #22 AWG
Approvals	NSF Certified, NSF/ANSI/CAN 61, RoHS

Wiring



How To Order

Specify Part Number based on flow rate measuring capability.



Flow Range		Frequency Out	Pulses Per Gallon	Pulses Per Liter	Part Number
GPM	LPM				
0.2 to 2	0.8 to 7.6	34 to 343 Hz	10,313	2724	226000 ⚡
0.4 to 4	1.5 to 15	29 to 343 Hz	4,994	1319	226100 ⚡

⚡ – Stock Items.




NSF approved

Dimensions



K-factor Chart* - Part Number 226000



* Consult factory for P/N 226100 K-factor chart

Pressure Drop—Typical

