



STVF...ES BENEFIT®

Modello	Type	STVF	47ES	67ES	75ES	93ES	100ES	-	139ES	157ES	-	210ES	-	278ES	-	-	-	-
Potenza	Capacity	ΔT 15K	W	470	665	745	925	1000	-	1385	1565	-	2085	-	2770	-	-	-
Assorbimento totale	Total consumption	1~230 V 50 Hz	W	10	10	10	23	10	-	23	20	-	20	-	46	-	-	-
			A	0,13	0,20	0,13	0,26	0,20	-	0,26	0,26	-	0,4	-	0,52	-	-	-
Peso	Weight		kg	1,6	1,9	2,5	2,3	3,1	-	3,9	4,9	-	6,1	-	7,7	-	-	-
ENERGY SAVING				125	130	125	65	130	-	65	250	-	260	-	130	-	-	-

STVF

Modello	Type	STVF	47	67	75	93	100	124	139	157	194	210	273	278	370	400	520	546	
Potenza	Capacity	ΔT 15K	W	470	665	745	925	1000	1235	1385	1565	1935	2085	2730	2770	3670	4000	5210	5460
Assorbimento totale	Total consumption	1~230 V 50 Hz	W	29	30	29	33	30	45	33	58	45	60	65	66	90	70	140	130
			A	0,18	0,20	0,18	0,21	0,20	0,32	0,21	0,36	0,32	0,40	0,44	0,42	0,64	0,30	0,60	0,88
Peso	Weight		kg	2,1	2,4	3	2,8	3,6	3,5	4,4	5,9	5,5	7,1	8,1	8,7	10,9	14	14	15,7
Note	Note		●■	●■	●■	▲■	●■	▲■	▲■	●■	▲■	●■	▲	▲■	▲■	●	●	▲	
DATI COMUNI / COMMON DATA																			
Elettroventilatori	Fans	n° x Ø mm	1x 170	1x 200	1x 170	1x 230	1x 200	1x 254	1x 230	2x170	1x 254	2x200	1x 275	2x230	2x254	1x 330	1x 330	2x275	
Portata d'aria	Air quantity	m³/h	255	330	220	450	290	650	390	440	570	580	900	780	1140	1100	1700	1800	
Livello pressione sonora	Sound pressure level	db(A)	29	34	29	36	34	40	36	32	40	37	40	39	43	39	43	43	
Superficie	Surface	m²	0,55	0,75	1,1	1	1,5	1,25	2	2,35	2,5	3,2	3,5	4,4	5,5	5,48	5,48	7,0	
Volume interno	Internal volume	dm³	0,13	0,18	0,26	0,25	0,36	0,3	0,5	0,56	0,6	0,75	0,78	0,97	1,22	1,23	1,23	1,56	
		mm	185	215	185	245	215	275	245	395	275	455	335	515	575	435	435	675	
Dimensioni	Dimensions	A	mm	184	214	184	244	214	274	244	184	274	214	304	244	274	380	380	304
		B	mm	30	30	60	30	60	30	60	60	60	60	60	60	60	60	60	60
		C	mm	141	143	171	148	173	152	178	171	182	173	215	178	182	255	255	215
		D	mm	30	30	30	35	30	35	30	35	30	30	-	35	35	-	-	-
		E	mm	45	47,5	75	48	77,5	49	78	75	79	77,5	-	78	79	-	-	-
		F	mm	40	41,5	52	44,5	54,5	45,5	57,5	52	58,5	54,5	-	57,5	58,5	-	-	-
		G	mm	214	238	214	268	238	298	268	428	299	476	-	536	596	-	-	-
		H	mm	230	254	230	284	254	314	284	444	314	492	-	552	612	-	-	-
		L	mm	92	93,5	122	99	123,5	101	129	122	131	123,5	-	129	131	-	-	-
Attacchi	Connections	Ø mm	8	8	8	8	8	8	8	8	8	8	8	8	8	15,5	15,5	15,5	

Note / Note

- Versione standard / Standard version 1~230V 50Hz / 60Hz
- ▲ Versioni speciali / Special versions 1~230V 60Hz
- Versioni speciali / Special versions 1~115V 60Hz

