

FHA ANGLED UNIT COOLER

1.1 kW to 8.3 kW



For small cold rooms

- 1 to 4 fans; fan diameter 275 mm
- Available with EC fan motors
- CO₂, Glycol and NH₃ (Ammonia) models also available
- Drain pan heater included with coolers with 7mm fin spacing



To order natural defrost (N) or electric defrost (E), add the letter N or E before the last digits of the model number (eg. FHA-30-N32 or FHA-30-E32)

FHA Unit Coolers

Fin Spacing **3 mm**



PART NUMBER	RATING (R404A) (W)		No. Fans	Air Throw (m)	DIMENSIONS (MM)		
	TC 2.5C, DT1 10K	TC 0C, DT1 8K			Width	Depth	Height
FHA-30-32	1650	1200	1	8	605	540	260
FHA-40-32	2050	1500	1	8	730	540	260
FHA-60-32	3350	2500	2	9	930	540	260
FHA-80-32	4150	3050	2	9	1180	540	260
FHA-120-32	6300	4650	3	10	1630	540	260
FHA-160-32	8250	6100	4	11	2080	540	260

FHA Unit Coolers

Fin Spacing **4.5 mm**



PART NUMBER	RATING (R404A) (W)		No. Fans	Air Throw (m)	DIMENSIONS (MM)		
	TC 2.5C, DT1 10K	TC 0C, DT1 8K			Width	Depth	Height
FHA-21-50	1450	1050	1	9	605	540	260
FHA-27-50	1800	1350	1	9	730	540	260
FHA-41-50	2950	2200	2	10	930	540	260
FHA-53-50	3600	2650	2	10	1180	540	260
FHA-79-50	5500	4050	3	11	1630	540	260
FHA-106-50	7350	5450	4	12	2080	540	260

FHA Unit Coolers

Fin Spacing **7 mm**



PART NUMBER	RATING (R404A) (W)		No. Fans	Air Throw (m)	DIMENSIONS (MM)		
	TC 2.5C, DT1 10K	TC 0C, DT1 8K			Width	Depth	Height
FHA-14-80	1130	850	1	10	605	540	260
FHA-17-80	1370	1000	1	10	730	540	260
FHA-28-80	2270	1700	2	11	930	540	260
FHA-35-80	2730	2000	2	11	1180	540	260
FHA-52-80	4260	3150	3	12	1630	540	260
FHA-70-80	5730	4250	4	13	2080	540	260



For datasheets, visit www.hawco.co.uk/fha

EG ANGLED UNIT COOLER

0.9 kW to 6.1 kW



For cold rooms

- 1 to 4 fans; fan diameter 250 mm
- High quality electrical heater included
- Fans with IP41 or IP44 protection
- Robust powder-coated steel casing for corrosion prevention

EG Unit Coolers with Electric Defrost

Fin Spacing **4 mm**

**KAR
YER** | HEAT
EXCHANGERS

	RATING (R404A) (W)		No. Fans	Air Throw (m)	DIMENSIONS (MM)			Equivalent LU-VE Model
	TC OC, DT1 8K				Width	Depth	Height	
EG-125AC4-C23-C24	1300		1	4.9	900	685	245	FHA-30-32
EG-125AE4-C23-C18	1600		1	4.2	900	685	245	FHA-40-32
EG-225AC4-C23-C8	2800		2	6.6	1500	685	245	FHA-60-32
EG-225AE4-C23-C12	3050		2	5.6	1500	685	245	FHA-80-32
EG-325BE4-C23-C12	4650		3	7.1	1380	685	370	FHA-10-32
EG-425BE4-C23-C10	6100		4	8.3	1740	685	370	FHA-160-32

EG Unit Coolers with Electric Defrost

Fin Spacing **4 mm**

**KAR
YER** | HEAT
EXCHANGERS

	RATING (R404A) (W)		No. Fans	Air Throw (m)	DIMENSIONS (MM)			Equivalent LU-VE Model
	TC OC, DT1 8K				Width	Depth	Height	
EG-125AB4-C23-C18	1100		1	5.3	900	685	245	FHA-21-50
EG-125BC4-C23-C20	1400		1	4.9	660	685	370	FHA-27-50
EG-225AB4-C23-C8/2	2200		2	7.2	1500	685	245	FHA-41-50
EG-225AC4-C23-C8	2800		2	6.6	1500	685	245	FHA-53-50
EG-325BC4-C23-C10	4100		3	8.3	1380	685	370	FHA-79-50
EG-425BC4-C23-C8	5400		4	9.7	1740	685	370	FHA-106-50

EG Unit Coolers with Electric Defrost

Fin Spacing **7 mm**

**KAR
YER** | HEAT
EXCHANGERS

	RATING (R404A) (W)		No. Fans	Air Throw (m)	DIMENSIONS (MM)			Equivalent LU-VE Model
	TC OC, DT1 8K				Width	Depth	Height	
EG-125BB7-C23-C30	900		1	5.7	660	685	370	FHA-14-80
EG-125AB7-C23-C18	1000		1	5.7	900	685	245	FHA-17-80
EG-225AB7-C23-C8/2	1900		2	7.7	1500	685	245	FHA-28-80 FHA-35-80
EG-325AC7-C23-C6	3500		3	8.9	2100	685	245	FHA-52-80
EG-425AC7-C23-C4/4	4800		4	10.5	2700	685	245	FHA-80



For technical data & pricing, visit www.hawco.co.uk/karyer