



* (See note)



Esempio di ordinazione / Ordering example
Exemple de commande / Typenschlüssel

SHF **50S** **N**

Ejemplo de pedido / Примерзаказа
Nomenklatura

S = Super
H = Hitec®
F = Fine / Thin / Mince / Dünn
Delgado / Тонкий/ Niewielki

Modello Modele Modelo Model	Type Model Модель
--------------------------------------	-------------------------

N = Sbrinamento ad aria Air defrost Dégivrage a air Luftabtauung Air descongelación Оттайка воздухом Odszranianie powietrzem	E = Sbrinamento elettrico Electric defrost Dégivrage électrique Elektrische Abtauung Desescarche eléctrico Электрическая оттайка Odszranianie elektryczne
---	--



410 - 570 W





★ (See note)

5.5 mm Passo alette Fin spacing			TC > 0 °C					
Modello	Type	SHF	50S	60S	70S	55D	65D	
Potenza Capacity	(R404A) (•) TC 2,5 °C (ΔT1 10K)	W	410	480	570	470	560	
		TC 0 °C (ΔT1 8K)	W	300	350	420	340	410
Portata d'aria	Air quantity	m³/h	190	210	280	240	265	
Freccia d'aria	Air throw	m	3,1	3,4	2,9	2x2,0	2x2,2	
Elettroventilatori	Fans	Ø 154 mm	n°	1	1	2	2	
Assorbimento motori Motor power consumption	1~230 V 50 Hz	W	30	30	60	60	60	
		A	0,24	0,24	0,48	0,48	0,48	
Sbrinamento	Defrost	E 230 V	W	330	450	450	330	450
Dimensioni	Dimensions	A	mm	382	472	472	382	472
		B	mm	350	440	440	350	440
Attacchi entrata	Inlet connections	Ø mm	8	8	8	8	8	
Volume circuito	Circuit volume	dm³	0,37	0,46	0,46	0,37	0,46	
Superficie esterna	External surface	m²	1,30	1,65	1,65	1,30	1,65	
Superficie interna	Internal surface	m²	0,16	0,20	0,20	0,16	0,20	
Peso	Weight	kg	3,9	4,6	5,6	4,7	5,6	

(•) Per altre condizioni vedere diagrammi (•) For other conditions see diagrams



SHF...S
Flusso singolo
Single discharge
Simple flux
Einseitig ausblasend
Flujo único
Однопоточные
Jednostronny wyrzut



*** SHF...D**
Doppio flusso
Dual discharge
Double flux
Zweiseitig ausblasend
Doble flujo
Двухпоточные
Dwustronny wyrzut

Bacinella

La bacinella è smontabile per rendere reversibile la posizione del tubo di scarico.

Drain Tray

The drain tray supplied with each model is reversible to enable the drain connector to be placed in the best location for water drainage within the cabinet.

Egouttoir

L'égouttoir est mobile pour permettre l'inversion du tuyau d'écoulement.

Tropfwanne

Abnehmbare Tropfwanne zur Schwenkung des Ablaufrohrs.

Bandeja de goteo

La bandeja es extraíble para invertir la posición del tubo de descarga.

Поддон

Сливной поддон снимается, таким образом, положение сливной трубы может меняться.

Taca ociekowa

Taca jest zdejmowana, aby ułatwić odwrócenie rury odpływowej.