



Classification : Preliminary Specification for Compressor Containing designed-theoretical value		Written By		Nutsanun Jeenpetch	
		Approved By		Korakot Intraratat	
Subject : DPW36FBAMTS		Issued Date		2021-04-19	
		Document No.		PL20-0225	
				Revised B	
1.Compressor data					
Type		Scroll			
Displacement	cm ³ /rev.	36.1			
	in ³ /rev.	2.2			
2.Motor data					
Motor type		BLDCM			
Motor protection		External			
Nominal output	W	1800			
Number of pole		4			
Nominal revolution	rpm	3600 (at 60rps)			
Insulation class		E			
Motor resistance (20 °C)	Ohm	1.45			
3.Refrigerant					
Type		R-290			
4.Oil					
Type		PZ46M			
Charge amount	L (in ³)	0.65 (39.7)			
5.Mass (include.oil)	kg (lbs)	21.6 (47.6)			
6.Compressor power source					
Rated voltage	V	107-400			
Rated frequency	Hz	120 (60rps)			
Running frequency	Hz	30-200 (15-100rps)			
Phase	∅	3			
7.Performance					
Refrigerating capacity (±5%)	W	6950	1500	3980	
	BTU/hr	23713	5118	13580	
Motor input (±5%)	W	2060	1290	1680	
COP	W/W	3.37	1.16	2.37	
EER	BTU/hr.W	11.51	3.97	8.08	
Current	A	6.1	4.5	5.3	
Note: Conditions		ARI	LT	MT	
Evaporating temp.	°C (°F)	7.2 (45.0)	-35 (-31.0)	-10 (14.0)	
Condensing temp.	°C (°F)	54.4 (129.9)	40 (104.0)	45 (113.0)	
Return gas temp.	°C (°F)	18.3 (64.9)	20 (68.0)	20 (68.0)	
Ambient temp.	°C (°F)	35.0 (95.0)	35 (95.0)	35 (95.0)	
Liquid temp.	°C (°F)	46.0 (114.8)	40 (104.0)	45 (113.0)	
Power source	rps/Hz	60/120	60/120	60/120	
Modulation		PWM(Sine wave), carrier frequency 4kHz			
Cooling performance curve		SCI-CPDD061			
-Performance data are base on SCI's calorie meter at oil 650 cc.					
Please follow to the general specification for DPW (TDRD13F039)					



Classification : Preliminary Specification for Compressor	Issued Date	2021-04-19
Subject : DPW36FBAMTS	Document No.	PL20-0225
Outline drawing	9G01D120	
Wiring diagram	CS01D584	
Crank case heater		25 W
Terminal parts accessories		
Terminal parts assy	CS01F449	
Terminal cover	SC25C057H01	1 pce.
Rubber bush	CR32D639H01	1 pce.
Mounting accessories		
Mounting parts	SC01D525	
Rubber mount	SC31D009H01	4 pcs.
Spacer (Optional)	SC10D377H01	4 pcs.
Motor parameter	TDRD20W036	
Observance matter of the compressor	TDRD20K002	

Developed-stage model



Classification : Preliminary Specification for Compressor	Issued Date	2021-04-19
Subject : DPW36FBAMTS	Document No.	PL20-0225
Pressure		
Condensing	2.02 MPaG [293 psiG] or less	
Evaporating	0.01 ~ 0.54 MPaG [1.5~78.3 psiG]	
Compression ratio	-	
Abnormal rise in pressure	-	
Temperature		
Condensing	Under 60 °C	
Evaporating temperature	-40 ~ 10 °C	
Discharge gas (max)	110 °C	
Suction gas superheat	Must be more than 0 °C - No liquid-back	
Discharge gas superheat	10 °C or more	
Outdoor ambient temp.	Under 43 °C	
Electrical		
Reverse phase (rotation)	Not possible	
ON / OFF		
ON/OFF frequency	Less than 250,000 cycles	
ON/OFF cycle	-The ON/OFF cycle shall be a maximum of 10 times/hour. -OFF time shall be the time until the high side and low side pressure reach to balance pressure (more than 3 minutes)	
Piping stress	3.5 kg/mm ² or less at start and stop condition (1.8 kg/mm ² during operation)	
Refrigerant circuit		
Maximum refrigerant charge	6 kg	
	No accumulator <2 kg	
Piping vibration	Maximum 0.8 mm.	
Inclination of compressor	Within 1°	