

Electrical equipment

Compressor [*with oil cooler connector]	Code number	Application	ASHRAE Capacity [W]						ASHRAE						Displacement	Voltage and frequencies [*dual frequency type with 50/60 Hz]	Compressor cooling [refer to data sheet]			
			Tc=54.4°C, Tlqg=32.2°C, Tsuc=32.2°C Evaporating temperature [°C]						LBP rating point -23.3°C / 54.4°C			MBP rating point -6.7°C / 54.4°C								
			-35	-15	-5	0	10	15	Cooling capacity	COP	Cooling capacity	COP	Cooling capacity	COP						
			[W]	[W/W]	[W]	[W/W]	[W]	[W/W]	[cm³]											
PL20F	101G0100	MBP	—	45	81	103	—	—	24	0.55	66	1.08	—	—	1.41	198–254 V, 50 Hz	S			
PL50F	101G0220	LBP	18	92	—	—	—	—	56	0.89	—	—	—	—	2.50	198–254 V, 50 Hz	S			
PL50F	101G0222	MBP	—	92	149	184	—	—	56	0.92	123	1.37	—	—	2.50	198–254 V, 50 Hz	F1			
PL50F	101G0223	MBP	—	92	149	184	—	—	56	0.92	123	1.37	—	—	2.50	198–254 V, 50 Hz	F1			
TL2.5F	102G4200	L/MBP	—	81	136	170	—	—	46	0.80	112	1.31	—	—	2.61	198–254 V, 50 Hz	S			
TL3F	102G4300	L/MBP	—	101	171	214	—	—	59	0.85	141	1.32	—	—	3.13	198–254 V, 50 Hz	S			
TL4F	102G4400	LBP	38	133	—	—	—	—	84	0.98	—	—	—	—	3.86	198–254 V, 50 Hz	S			
TL5F	102G4501	LBP	53	178	—	—	—	—	113	1.06	—	—	—	—	5.08	198–254 V, 50 Hz	S			
TLS5F	102G4520	LBP	59	210	—	—	—	—	134	1.15	—	—	—	—	5.08	198–254 V, 50 Hz	S			
TLS6F	102G4620	LBP	72	227	—	—	—	—	143	1.14	—	—	—	—	5.70	198–254 V, 50 Hz	S			
TLS7F	102G4720	LBP	82	257	—	—	—	—	164	1.15	—	—	—	—	6.49	198–254 V, 50 Hz	S			
TLES3F	102G4310	L/MBP	—	115	192	240	—	—	70	1.07	158	1.57	—	—	3.13	198–254 V, 50 Hz	S			
TLES4F	102G4410	LBP	41	154	—	—	—	—	97	1.16	—	—	—	—	3.86	198–254 V, 50 Hz	S			
TLESSF	102G4510	LBP	62	210	—	—	—	—	134	1.22	—	—	—	—	5.08	198–254 V, 50 Hz	S			
TLES6F	102G4610	LBP	72	227	—	—	—	—	143	1.20	—	—	—	—	5.70	198–254 V, 50 Hz	S			
TLES5.7FT.3	102G4573	LBP	82	248	—	—	—	—	163	1.30	—	—	—	—	5.70	187–254 V, 50 Hz	S			
TLES6FT.3	102G4609	LBP	82	248	—	—	—	—	163	1.30	—	—	—	—	5.70	187–254 V, 50 Hz	S			
TFS4.5FT	102G4433	LBP	56	193	309	—	—	—	123	1.12	256	1.65	—	—	4.63	176–242 V, 50 Hz	S			
TLS3FT	102G4325	LBP	26	115	—	—	—	—	69	1.07	—	—	—	—	3.13	187–254 V, 50 Hz	S			
TLS4FT	102G4424	LBP	34	145	—	—	—	—	88	0.97	—	—	—	—	3.86	187–254 V, 50 Hz	S			
TLS5FT	102G4524	LBP	59	210	—	—	—	—	134	1.12	—	—	—	—	5.08	187–254 V, 50 Hz	S			
NL6F	105G6606	LBP	64	247	—	—	—	—	152	1.22	—	—	—	—	6.13	198–254 V, 50 Hz	S			
NL7F	105G6706	LBP	87	294	—	—	—	—	187	1.21	—	—	—	—	7.27	198–254 V, 50 Hz	S			
NL8F	105G6822	LBP	100	307	—	—	—	—	201	1.24	—	—	—	—	7.95	198–254 V, 50 Hz	S			
NL9F	105G6802	LBP	92	332	—	—	—	—	213	1.21	—	—	—	—	8.35	198–254 V, 50 Hz	S			
NLE9F	105G6805	LBP	101	335	—	—	—	—	211	1.33	—	—	—	—	8.35	198–254 V, 50 Hz	S			
NL11F	105G6900	LBP	126	435	—	—	—	—	274	1.22	—	—	—	—	11.15	198–254 V, 50 Hz	F2			
NF9FX	105G6841	L/MBP	113	356	575	715	—	—	229	1.09	475	1.59	856	2.28	8.34	198–242 V, 50 Hz	F1			
NF11FX	105G6944	L/MBP	141	454	725	898	—	—	294	0.97	600	1.41	1070	2.02	11.15	198–242 V, 50 Hz	F2			
NL6.1FT	105G6620	LBP	74	245	—	—	—	—	157	1.21	—	—	—	—	6.13	187–254 V, 50 Hz	S			
NL7FT	105G6718	LBP	88	290	—	—	—	—	186	1.22	—	—	—	—	7.27	187–254 V, 50 Hz	S			
NL7.3FT	105G6726	LBP	88	290	—	—	—	—	186	1.22	—	—	—	—	7.27	187–254 V, 50 Hz	S			
NL8.4FT	105G6055	LBP	107	340	—	—	—	—	220	1.23	—	—	—	—	8.35	187–254 V, 50 Hz	F1			
NL9FT	105G6828	LBP	107	340	—	—	—	—	220	1.23	—	—	—	—	8.35	187–254 V, 50 Hz	S			
NL10FT	105G6188	LBP	141	434	—	—	—	—	284	1.25	—	—	—	—	10.09	187–254 V, 50 Hz	S			
NL11MF	105G6156	M/HBP	—	471	756	938	1400	1687	—	—	626	1.61	1121	2.19	11.15	187–254 V, 50 Hz	F2			
NLE10MF	105G6888	MBP	110	425	687	854	—	—	268	1.28	568	1.71	1023	2.32	10.09	198–254 V, 50 Hz	F1			
NLE10MF.2	105G6187	L/MBP	116	457	735	914	1372	—	290	1.45	608	1.94	1097	2.61	10.09	198–254 V, 50 Hz	F2			
NLE11MF.2	105G6197	MBP	—	513	821	1018	1509	—	331	1.41	680	1.88	1211	2.50	11.15	198–242 V, 50 Hz	F2			
FR11G	103G6980	L/M/HBP	—	380	621	780	—	—	236	1.10	513	1.50	—	—	11.15	187–254 V, 50 Hz	F1			
SC15F	104G8500	LBP	126	545	901	—	—	—	324	1.11	745	1.59	—	—	15.28	198–254 V, 50 Hz	F1			
SC15MFX	104G8501	MBP	—	569	951	1185	1749	—	326	1.10	785	1.66	1408	2.31	15.28	198–254 V, 50 Hz	F2			
SC18F	104G8800	LBP	159	640	1041	—	—	—	389	1.17	863	1.62	—	—						