


# CEILING CONCEALED DUCT

LOW STATIC PRESSURE  
- CL09F / CL12F / CL18F / CL24F

UUA1 ULO

UUB1 U20

UUC1 U40



LG participates in the ECP programme for EUROVENT AC program.  
Check ongoing validity of certification  
: [www.eurovent-certification.com](http://www.eurovent-certification.com)

					Only 460mm deep			
COMBINATION					9	12	18	24
Capacity	Cooling	Min. / Rated / Max.	kW		1.5 / 2.5 / 3.2	1.5 / 3.4 / 4.7	2.0 / 5.0 / 5.8	2.7 / 6.8 / 7.8
	Heating	Min. / Rated / Max.	kW		1.8 / 3.2 / 4.0	1.8 / 4.0 / 4.9	2.3 / 5.8 / 6.7	3.0 / 7.5 / 9.0
Power Input (Set)	Cooling	Min. / Rated / Max.	kW		0.30 / 0.67 / 0.93	0.33 / 1.05 / 1.84	0.3 / 1.35 / 1.89	0.4 / 2.03 / 2.84
	Heating	Min. / Rated / Max.	kW		0.38 / 0.75 / 1.63	0.33 / 1.08 / 1.63	0.4 / 1.77 / 2.48	0.4 / 2.13 / 3.30
Running Current	Cooling	Rated	A		3.0	4.7	7.5	9.0
	Heating	Rated	A		3.3	4.8	8.3	9.4
EER / COP			kWh / kWh		3.80 / 4.30	3.23 / 3.71	3.71 / 3.28	3.35 / 3.52
SEER / SCOP			kWh / kWh		6.1 / 4.0	5.6 / 3.8	6.1 / 3.9	6.2 / 3.9
Pdesign	Cooling @ 35°C		kW		2.5	3.4	5	6.8
	Heating @ -10°C		kW		2.9	2.9	4.1	5.4
Seasonal Energy Label	Cooling / Heating		-		A+ / A+	A+ / A	A++ / A	A++ / A
Annual Energy Consumption	Cooling / Heating		kWh		143 / 1,015	213 / 1,068	287 / 1,472	384 / 1,938
Dehumidification Rate			l/h		0.2	0.8	1.6	2.5
ODU Sound Pressure Level	Cooling / Heating	Rated	dB(A)		49 / 52	49 / 52	47 / 52	48 / 52
ODU Sound Power Level	Cooling	Rated	dB(A)		65	65	63	65
Piping Connections	Liquid		mm (inch)		Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø9.52 (3/8)
	Gas		mm (inch)		Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)	Ø15.88 (5/8)
	Connections Method		-		Flared	Flared	Flared	Flared
Operation (Outdoor)	Range Cooling	Min. / Max.	°C		-15 / 50	-15 / 50	-15 / 50	-20 / 50
	Heating	Min. / Max.	°C		-20 / 18	-20 / 18	-20 / 18	-20 / 18
INDOOR					CL09F N50	CL12F N50	CL18F N60	CL24F N30
Power Supply			Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Input (IDU)		H / M / L	W		21 / 15 / 13	21 / 15 / 13	100 / 90 / 80	150 / 130 / 110
Air Flow Rate		H / M / L	m³/min		11.5 / 9.5 / 8	11.5 / 9.5 / 8	15 / 12 / 10	20 / 16 / 12
Dimensions	Body	W x H x D	mm		900 x 190 x 460	900 x 190 x 460	1,100 x 190 x 460	1,100 x 190 x 700
Weight	Body		kg		18.0	18.0	20.9	26.0
Sound Pressure Level	Cooling	H / M / L	dB(A)		35 / 30 / 27	35 / 30 / 27	34 / 31 / 29	39 / 35 / 32
Sound Power Level	Cooling	Max.	dB(A)		55	55	56	58
Piping Connections	Drain	O.D. / I.D.	mm		Ø320 / 26.0	Ø320 / 26.0	Ø320 / 26.0	Ø320 / 26.0

OUTDOOR					UUA1 ULO	UUB1 U20	UUC1 U40
Power Supply			Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker		Min.	A		15	20	25
Power Supply Cable (Included Earth)			No x mm³		3C x 1.5	3C x 2.5	3C x 2.5
Dimensions	Net	W x H x D	mm		770 x 545 x 288	870 x 650 x 330	950 x 834 x 330
Weight	Net		kg		33.3	44.5	57.7
Compressor	Type		-		Twin Rotary	Twin Rotary	Twin Rotary
	Type		-		R32	R32	R32
Refrigerant	GWP (Global Warming Potential)		-		675	675	675
	Precharged Amount		kg		1.0	1.2	1.9
	t-CO <sub>2</sub> eq		-		0.675	0.81	1.283
	Additional Charge (After 7.5m)		g/m		20	20	40
Fan	Air Flow Rate	Rated	m³/min x No.		28 x 1	50 x 1	58 x 1
Total Piping Length		Min. / Max.	m		5 / 30	5 / 30	5 / 50
Piping Elevation	IDU - ODU	Max.	m		30	30	30