AIR FILTERING

Air treatment and ventilation









Air treatment



Heat recovery units







With energy recovery.
Ventilation system with energy recovery. KPI-252~2002E4E / KPI-502~2002E4E

Heat recovery units with DX coils









With energy recovery.
Ventilation system with energy recovery and built-in DX coil.
KPI-502~1002X4E



DX kit







Control system for DX coil. Example of use: air handling unit with DX coil. EVX.2.0-10E2

Free cooling kit for ducted units





Fresh air solution for ducted units.

EF-456N1E

DX air curtains



Hitachi / Frico

- Hitachi and Frico have come together to offer DX air curtains compatible with the Hitachi units in the Prime/IVX range.

 The factory assembly of the expansion valves, control box and a lift pump allows for ultra-fast
- installation.
- Frico's Linea DXH and AZR DXH air curtain ranges combine with a Hitachi split heat pump for 3.5m high installations.

Functions

- The DX air curtain creates a thermal barrier all year round and provides comfort in both summer and winter with minimal energy expenditure.
 No need for a filter, with the microperforated
- intake grille.
- Max. air off temperature: 35°C.

Advantages

- Quick return on investment.
- Energy efficiency, reduced operating costs.
- Low CO₂ emissions.
- 2 versions available: recessed and surface mounted models.
- Model available in all RAL colors.
- Reversible range (heating or cooling operation).
 Also compatible with outdoor unit X-Premium.

Air curtains

2000





Outdoor units





RAS-3HVNC1

RAS-4H(V)NC2E

RAS-8HNCE RAS-10HNCE

Recessed curtain

Surface mounted curtain Recessed curtain Hitachi-compatible outdoor units Split installation: Compatible outdoor units (requires the remote control PC-ARFP1E) Linea M DXH compatible with Hitachi, height of up to 3 m, 230V~ AZR M DXH compatible with Hitachi, height of up to 3 m, 230V~ Utopia Prime / IVX Voltage Weight Power Voltage Weight Part number Part number kg kW Model Ref LINEAM1000DXH3 9 52 AZRM1000DXH3 52 RAS-3HVNC1 1560 230 1560 230 LINEAM1500DXH4 RAS-4H(V)NC2E 12 2170 230 83 AZRM1500DXH4 12 2170 230 83 LINEAM2000DXH6 18 3100 230 113 AZRM2000DXH6 18 3100 230 113 RAS-6H(V)NC2E LINEAM2500DXH8 145 AZRM2500DXH8 RAS-8HNCE

Linea G DXH compatible with Hitachi, height of up to 3.5 m, 230V~

AZR M DXH compatible with Hitachi, height of up to 3.5 m, 230V~

Part number	Power	Air flow rate	Voltage	Weight	Part number	Power	Air flow rate	Voltage	Weight	Utopia Prime / IVX
Faithumber	kW	m³/h	(V)	kg	Fait Hullibei	kW	m³/h	(V)	kg	Model Ref
LINEAG1000DXH4	12	2170	230	55	AZRG1000DXH4	12	2170	230	55	RAS-4H(V)NC2E
LINEAG1500DXH6	15	3100	230	85	AZRG1500DXH6	15	3100	230	85	RAS-6H(V)NC2E
LINEAG2000DXH8	22	4400	230	115	AZRG2000DXH8	22	4400	230	115	RAS-8HNCE
LINEAG2500DXH10	26	5450	230	147	AZRG2500DXH10	26	5450	230	147	RAS-10HNCE

Part number	Height	Length	Depth	Part number	Height	Length	Depth
LINEA1000DXH	140+260	1000	480	AZR1000DXH	130+260	1000	700
LINEA1500DXH	140+260	1500	480	AZR1500DXH	130+260	1500	700
LINEA2000DXH	140+260	2000	480	AZR2000DXH	130+260	2000	700
LINEA2500DXH	140+260	2500	480	AZR2500DXH	130+260	2500	700





Ventilation units

With energy recovery

ΑP




Functions and features


- Suitable for a wide variety of buildings applications.
- Option to connect a CO₂ sensor (not supplied) and automatically regulate air quality based on a pre-set maximum CO_2 concentration.
- High-efficiency F7 filters are available (optional).
- The Hitachi heat recovery ventilation system adjusts the temperature and humidity of incoming fresh air to match the indoor environment.
- Automatic ventilation mode where the KPI controls which mode to operate within to ensure maximum energy efficiency.
- Forced bypass mode where 100% fresh air is supplied for free cooling
- KPI units can alter a room's pressurisation level if required to either help keep air in or extract air depending on the requirement.

Advantages

- Temperature exchange efficiency up to 83%.
- Low-consumption electronic fan motors.
- Sound pressure from 25 dB(A).
- All insulation with these KPIs is M1-certified (NF-P92-501).
- Up to 240 Pa available static pressure.



KPI-252E4E KPI-502E4E KPI-802E4E KPI-1002E4E KPI-1502E4E KPI-2002E4E



Controls and compatible accessories (see the tab VRF TWIN controls)



KPI

Wired remote control weekly timer PC-ARFP1E

Noise attenuator

SLT-30-200-L600: Compatible with KPI-502E4E

SLT-30-250-L600: Compatible with KPI-802E4E

SLT-30-300-L600: Compatible with KPI-1002E4E

SLT-30-355-L600: compatible with KPI-1502-2002E4E



High-efficiency filter
HEF-252:
Compatible with KPI-252E4E
HEF-502:

HEF-502: Compatible with KPI-502E4E HEF-802:

Compatible with KPI-802E4E

HEF-1002: Compatible with KPI-1002E4E HEF-1502: Compatible with KPI-1502E4E HEF-2002:

Compatible with KPI-2002E4E

Ventilation with DX coil

200 Pa

With energy recovery



Functions and features

- System dedicated to the handling of fresh air.
- Suitable for a wide range of building applications, especially in areas with lower outside temperatures.
- Option to connect a CO_2 sensor (not supplied) and automatically regulate air quality based on a pre-set maximum CO₂ concentration.


 - High-efficiency F7 filters are available (optional).
- The Hitachi heat recovery ventilation system adjusts the temperature
- and humidity of incoming fresh air to match the indoor environment.


 Automatic ventilation mode where the KPI controls which mode to operate within to ensure maximum energy efficiency.
- Forced bypass mode where 100% fresh air is supplied for free cooling
- KPI units can alter a room's pressurisation level if required to either help keep air in or extract air depending on the requirement.


Advantages

- Temperature exchange efficiency up to 83%.
- Low-consumption electronic fan motors.
- All insulation in these KPIs is M1 certified (NF-P92-501).
- Compatible with Utopia IVX, Set Free Mini, Centrifugal, or VRF SIGMA.
- Sound pressure from 29 dB(A).
 Up to 200 Pa available static pressure.
- Heating capacity up to 13 kW.

KPI active







KPI-502X4E


KPI-802X4E


KPI-1002X4E

Celluloid paper heat Exchanger with DX coil	Unit	KPI-502X4E	KPI-802X4E	KPI-1002X4E
Nominal cooling capacity (recovery)	kW	5,32 (of which is recovered: 1.81)	7,96 (of which is recovered: 2.94)	10,83 (of which is recovered: 3.73)
Nominal heating capacity (recovery)	kW	6,92 (of which is recovered: 2.12)	9,79 (of which is recovered: 3.49)	12,93 (of which is recovered: 4.43)
Exchange efficiency (H / M / L)	%	74 / 77 / 78	75 / 76 / 78	78 / 81 / 83
Sound pressure level (H / M / L)	dB(A)	32 / 30 / 29	34 / 33 / 32	36 / 33 / 31
Airflow rate (H / M / L)	m³/h	500 / 430 / 380	800 / 700 / 590	1000 / 820 / 740
Available static pressure (H / M / L)	Pa	90 / 82 / 60	110 / 80 / 57	170 / 105 / 80
Maximum external pressure (nominal)	Pa	200	110	170
Dimensions (H x W x L)	mm	330 x 1435 x 920	385 x 1513 x 1015	385 x 1904 x 1295
Weight	kg	62	69	100
Power supply			1~230V 50Hz	
Recommended fuse size	А		5	10

Controls and compatible accessories (see the tab VRF TWIN controls)

Wired remote control weekly timer
PC-ARFP1E





DX kit

Air-handling unit.







The kit includes:

- 4 temperature sensors with extensions (THM1: air inlet sensor and THM2: air outlet sensor. THM3 and THM4: sensors at liquid
- 1 electronic expansion valve box.
- 1 electrical box.
- 1 harness jumper.

Not included:

- Remote control PCARFP1E.
- PCC-1A connectors.

Functions and features


- An "expansion valve / control box" kit that connects an Hitachi unit to a 3rd party system with a DX heat exchanger coil (AHU, ventilation, air curtain, etc.) and manages it like an Hitachi indoor unit.
- Modular operation: Combine up to 5 DX interfaces to works as a group on the same DX coil (up to 50HP with outdoor unit IVX PREMIUM only). The Master unit has 4 temperature sensors. Slave units have only gas and liquid sensors (heat exchanger pipes).
- Synchronized defrosting between the units.
- Precise temperature: the combination of the DX kit with RAS-XH(V)NP1E guarantees the highest levels of precision on the market in terms of maintaining the target temperature.
- The control of capacity demand can be done by inlet air temperature, outlet air temperature, incremental reference duty control and absolute reference duty control, depending on the needs of the installation

Important

- Do not stop the air flow through the DX coil while defrosting the outdoor units. You can add an electrical heater battery to avoid blowing cold air (not managed or sold by Hitachi). A 12Vdc relay (not sold by Hitachi) to serve the heater battery must be provided.
- 12Vdc relay must be used for heating/cooling mode selection if the AHU has inputs to select heating/cooling mode. - If the AHU has outputs for managing the mode (heating/cooling), these must connect to the inputs (dry contact) of the outdoor unit.

DX kit





Control



Outdoor units

RAS-4XH(V)NP1E RAS-5XH(V)NP1E RAS-6XH(V)NP1E RAS-8XHNPE RAS-10XHNPE


Expansion valve box

Extended DX coil operating range

T° of DX coil air inlet

(Installation with X PREMIUM unit)

T° of DX coil air inlet (Installation IVX Prime, IVX Comfort, SET FREE MINI and SIGMA).




 $Below \ these \ values, provide \ an \ electrical \ heater \ battery \ or \ a \ heat \ recovery \ system \ upstream \ of \ the \ DX \ coil.$

Ultimate control

- Compatible with X PREMIUM units RAS-4~10XH(V)NP1E only.
- A 0-10V, 0-5V/4-20mA input for external control can be utilised.
- Capacity control possible on the return or supply air temperature.
- External control with a 0-10V signal to precisely control the frequency of the compressor.
- Compatible with units IVX Prime, IVX Comfort and FREE Mini and SIGMA units.
- Control based on return air only.



Temperature of the supply air, return, etc.



Optimal defrosting

- Installation with 3 units: only one unit in defrosting mode.
- Installation with 5 units: 2 units in defrosting mode and 3 units operating.

DX kit

Part number of DX KIT		EXV-2.0E2	EXV-2.5E2	EXV-3.0E2	EXV-4.0E2	EXV-5.0E2	EXV-6.0E2	EXV-8.0E2	EXV-10.0E2
Nominal Cooling capacity	kW	5.0	6.0	7.1	10.00	12.50	14.00	20.00	25.00
Nominal Heating capacity	kW	5.6	7.0	8.0	11.20	14.00	16.00	22.40	28.00
Control box									
Colour	-				Natural Gray (Mu	insell 1.0Y8.5/0.5)			
Dimensions (H x W x D)	mm				291 x 34	41 x 127			
Weight	kg				;	3			
Power supply	-		1~230 V 50hz						
Max. fan current	А				3	.5			
Expansion valve box									
Dimensions (H x W x D)	mm				431 x 19	99 x 103			
Weight	kg	2.0			2.7			4	.5
Pipe diameter (Liq.)	inches	1/4				3/8			
Remote control (not included)	-	PC-ARFP1E							
Outdoor unit	Нр	2	2.5	3	4.0	5.0	6.0	8.0	10.0
		Ask technical for details	Ask technical for details	RAS-3XHVNP1E	RAS-4XH(V)NP1E	RAS-5XH(V)NP1E	RAS-6XH(V)NP1E	RAS-8XHNPE	RAS-10XHNPE

COMPATIBILITY TABLE FOR DX KITS WITH OUTDOOR UNITS

		Allowed H	eat exchanger ca	pacity (kW)	Heat Ex	changer inner vo	olume (L)	Recommended	l Airflow (m³/h)
DX kit part no.	Mode	Min	Nominal	Max	Min	Max	Max Outdoor unit X-Premium only	Min	Max
EXV-2.0E2	Cooling Heating	4.0 4.5	5.0 5.6	5.6 7.1	0.57	1.16	-	480	1260
EXV-2.5E2	Cooling Heating	4.8 5.6	6.0 7.0	6.3 7.1	0.89	1.35	-	690	1560
EXV-3.0E2	Cooling Heating	5.7 6.4	7.1 8.0	9.0 11.2	1.03	1.57	2.89	750	1800
EXV-4.0E2	Cooling Heating	8 9	10 11.2	11.2 12.5	1.51	2.37	4.56	1200	2160
EXV-5.0E2	Cooling Heating	10 11.2	12.5 14	14 16	1.92	2.37	4.56	1380	2490
EXV-6.0E2	Cooling Heating	11.2 12.8	14 16	16 18	1.92	2.92	5.11	1500	2550
EXV-8.0E2	Cooling Heating	16 17.9	20 22.4	22.4 25	2.92	3.89	6.93	3540	4680
EXV-10.0E2	Cooling Heating	20 22.4	25 28	28 31.5	3.89	4.76	10.73	4080	5340

The capacity of the heat exchanger must match the specified rated capacity of each DX KIT under the following temperature conditions. Failure to comply with the heat exchanger's capacity can result in a system malfunction. Data applies under the following conditions:

Nominal conditions	Heating mode	Nominal conditions	Cooling mode
Indoor air inlet temperature	20°C(DB)	Indoor air inlet temperature	27°C(DB)/19°C(WB)
Outdoor temperature	7°C(DB)/6°C(WB)	Outdoor temperature	35°C(DB)
Condensing temperature	40°C ~ 45°C	Evaporation temperature	6°C
Subcooling temperature	3°C	Superheating temperature	5°C

(DB): dry bulb - (WB): wet bulb

Combination with VRF:

Combination with ver:

Control based on return air only.

Installing the VRF SIGMA as a single-split unit + DX KIT is not allowed.

It is possible to install several DX KITs (DX KIT only) with a SIGMA unit. But the maximum connection rate allowed is 100%.

With a combined installation of a DX KIT + Air/Air indoor units with VRF SIGMA, the connection rate is: 30% DX KIT and 70% Air/Air.

	Unit	RAS-4XH(V)NP1E	RAS-5XH(V)NP1E	RAS-6XH(V)NP1E	RAS-8XHNPE	RAS-10XHNPE	
Performance, cooling							
Nominal cooling capacity (min-max)	kW	10.0 (4.5-11.2)	12.5 (5.7-14.0)	14.0 (6.0-16.0)	20.0 (8.0-22.4)	25.0 (10.0-28.0)	
Rated power input cooling	kW	2.14	3.28	4.11	5.62	8.14	
EER	-	4.68	3.81	3.41	3.56	3.07	
Working range in Cooling outdoor unit	°C			-5 /+46			
Performance, heating							
Nominal heating capacity (min-max)	kW	11.2 (5.0-14.0)	14.0 (5.0-18.0)	16.0 (5.0-20.0)	22.4 (6.3-28.0)	28.0 (8.0-35.0)	
Rated power input heating	kW	2.17	3.08	3.78	5.32	7.29	
COP	-	5.16	4.55	4.23	4.21	3.84	
Working range in Heating outdoor unit	-			-20 /+15			
Technical features							
Airflow (cooling)	m³/h	4,800	5,400	6,000	7,620	8,040	
Sound pressure in Cooling mode (night mode)	dB(A)	47 (43)	48 (44)	48 (45)	57 (55)	58 (56)	
Sound pressure in Heating mode	dB(A)	49		50	59	60	
Sound power	dB(A)	63	64	65	76		
Net weight	kg		103		136	138	
Dimensions (H x L x D)	mm			1380 x 950 x 370			
Diameter of pipes (Liq / Gas)	inches		3/8 - 5/8		3/8 - 1 1/8	1/2 - 1 1/8	
Compressor	-			Scroll Inverter			
Refrigeration characteristics							
Min. pipe length	m			5			
Pre-charged for	m			30			
Initial refrigerant charge	kg	4.1	4.2	4.2	5.3	6	
Additional charge	Kg		calculate based on the meth	od indicated in the installatio	n technical documentation (1)		
Max. pipe length	m	75 100				00	
Expansion valve box installation	-			Within 5 m MAX of DX Coil			
Max. level difference (outdoor unit above / below)	m	30 / 20					
Refrigerant	-			R410A			
Technical features							
Power supply	-	:	3N ~ 400V 50Hz (1 ~ 230V 50Hz	z)	3N ~ 40	0V 50Hz	
Max. current	А	14.0	(30.5)	16.0 (30.5)			
Recommended fuse size	А	16	(32)	20 (32)	32		
Cable width (EN 60 335-1) (2)	mm²		5 x 2.5 (3 x 6.00)		5 x 6.00		

(1) The values of "Additional charge needed" are determined on a case by case basis. To find out these values, see the "DX interface coolant refill and max. pipe lengths" section listed in the Technical Catalogue. (2) Data shown is for indication purpose only. It is the installer's responsibility to ensure that these cable widths meet the needs of the facility and current standards.



Controls and compatible accessories (see the tab VRF TWIN controls)





Econofresh Free cooling for ducted units



Functions and features


- The EconoFresh is a module that is added to the return air of a RPI unit (sizes 4-6 HP only). It can supply up to 100% fresh air and is able to provide natural 'free cooling' through a set of dampers when the outdoor air temperature is lower than the set indoor temperature.


 - It can operate in conjunction with a CO2 sensor or an enthalpy sensor
- (taking into account latent heat) to ensure air quality in a room.


 The intelligent EconoFresh continuously modifies the damper opening
- to ensure the set point is always maintained, and where possible shut the compressor down to save on running costs and energy use.

Advantages

- Compatible with Utopia Prime, IVX Comfort / Set Free Mini / VRF Sigma / VRF Centrifugal.
- 3 standard speeds.3 adjustable levels of static pressure.
- Easily accessible filters.
- Automatic regulation (damper position and compressor speed).
 Free-cooling mode in mid-season.
- Potential 100% fresh air mid-season.
- 40% energy savings possible with use of EconoFresh compared to standard installations.







Econofresh kit



Medium-pressure ducted unit 150 Pa compatible with Econofresh

150Pa ducted indoor units	Unit	RPI-4.0FSN6E-EF	RPI-5.0FSN6E-EF	RPI-6.0FSN6E-EF
Power	Нр	4.00	5.00	6.00
Nominal Cooling capacity UTOPIA	kW	10.00	12.50	14.00
Nominal Heating capacity UTOPIA	kW	11.20	14.00	16.00
Nominal Cooling capacity SET FREE	kW	11.20	14.00	16.00
Nominal Heating capacity SET FREE	kW	12.50	16.00	18.00
Sound pressure (L / M / H) $^{(1)(3)}$	dB(A)	35 / 38 / 39	36 / 38 / 40	36 / 36 / 40
Sound power	dB(A)	62	64	64
Airflow (L/M/H)	m³/h	1680 / 2070 / 2160	1920 / 2100 / 2220	1950 / 2130 / 2250
Rated static pressure (min-max)	Pa	37 (0~150)	50 (0~150)	50 (0~150)
Condensate pump			Yes	
Max. elevation	mm		850	
Diameter of pipes (Liq/Gas)	inches		3/8 - 5/8	
Condensate outlet diameter (ext)	mm		32	
Dimensions (H x L x D)	mm		240 x 1474 x 600	
Weight	kg		42	
Power supply	-		1~ 230V 50Hz	
Cable width (EN 60 335-1) ⁽²⁾	mm²		3 x 0.75	
Max. current	А	3.2	3	.5
Recommended fuse size	А		5	
Remote control	-		PC-ARFP1E	

⁽¹⁾ Sound levels (pressure) are measured in an anechoic chamber at 1.50 m below the unit (no ceiling under the unit), with an extraction duct at 1 m and a discharge duct at 2 m. ⁽²⁾ Data shown is for indication purposes only. It is the installer's responsibility to ensure that these cable widths meet the needs of the facility. ⁽³⁾ Ultra high-speed access is possible with remote controls PC-ARFP1E (or PC-ARFG-E available second half of 2021) and PC-ARH1E.

Econofresh kit	Unit	EF-456N1E
Dimensions (H x L x D)	mm	254 x (1491 + 59) x 270
Weight	kg	13.7
Power supply	-	via the board of the indoor unit

