80

Light commerical wall mount









Multiple features to fit any setup



4-Way Swing

Because the blades move both vertically and horizontally, the air is distributed more uniformly, improving the level of comfort in the room. (Fig. 1)

Motion sensor

Technology that saves you money - with a motion sensor to continuously analyze the presence of people in the room.

If there is no detection after 20 min, the setpoint is shifted by one degree; after 40 min it shifts one degree again. (Fig. 2)

Improved comfort

With the SPX-WKT4 remote control, you can choose where to measure the setting temperature (at the remote control or the return or using the average of both readings). This feature improves $% \left(x\right) =\left(x\right) +\left(x\right) \left(x\right)$ the level of comfort in the room.

Flexible installation


With a 30 m long pipe run between the indoor unit and the outdoor unit, this indoor unit can be installed in any part of the building. What's more, the level difference between the two can be up to 20 m.


Compatible with the airCloud remote controller

In the app, you can turn the system on and off, turn the temperature up or down and program the system from anywhere in the world. All you need is a mobile phone, an Internet connection and Wi-Fi equipment (optional) to connect to the equipment.


A compact indoor unit

This indoor unit measures only 900 mm wide, so it can be installed anywhere without interfering with other elements in the room.









Outdoor units







Light commercial Wall units

Performance, cooling	Unit	5.0 kW	6.0 kW	7.0 kW
Nominal cooling capacity (min-max)	kW	5.00 (1.20 - 5.80)	6.00 (1.20 - 6.50)	7.00 (1.50 - 8.00)
JK cooling capacity (UK sensible)	kW	4.71 (3.30)	5.30 (3.67)	5.54 (4.49)
Rated power input Cooling (min-max)	kW	1.42 (0.30 - 2.500)	1.71 (0.30 - 2.65)	2.00 (0.50 - 2.70
EER	-	3.52	3.51	3.50
Energy class Cooling	-		A++	
SEER (average climate)	-	7.30	6.50	7.00
Norking range in Cooling	°C		-15°C /+ 46°C	
Performance, heating				
Nominal heating capacity (min-max)	kW	6.00 (1.20 - 6.80)	7.00 (1.20 - 8.00)	8.00 (1.50 - 8.50)
Heating capacity at -7°C ⁽¹⁾	kW	4.20	4.80	5.80
Rated power input Heating (min-max)	kW	1.50 (0.30 - 2.650)	1.84 (0.30 - 2.65)	2.10 (0.50 - 2.80
COP	-	4.00	3.80	3.81
Energy class Heating	-	A++	A+	A++
SCOP (average climate)	-	4.60	4.20	4.60
Norking range in Heating	°C	-15°C /+ 24°C		
ndoor units	Unit	RAK-50RPE1	RAK-60RPE	RAK-70PPD
Sound pressure in Cooling mode (EL / L / M / H) (2)	dB(A)	26 / 33 / 39 / 47	30 / 33 / 42 / 48	30 / 35 / 42 / 47
Sound pressure in Heating mode (EL / L / M / H) (2)	dB(A)	26 / 33 / 39 / 47	33 / 34 / 42 / 49	30 / 36 / 42 / 47
Sound power in Cooling mode	dB(A)		60	
Airflow in Cooling mode (EL / L / M / H)	m³/h	310 / 410 / 570 / 720	480 / 540 / 690 / 930	510 / 630 / 870 / 1020
Dehumidification	l/h	2.8		4.8
Dimensions (H x L x D)	mm	300 x 900 x 230		300 x 1100 x 260
Net weight	kg	12.0		15.0
Remote control	-	Not included		
Outdoor units	Unit	RAC-50NPE	RAC-60NPE	RAC-70NPD
Sound pressure in Cooling mode ⁽²⁾	dB(A)	50		52
Sound power in Cooling mode	dB(A)	65		67
Airflow (Cooling / Heating)	m³/h	2160 / 2160		2700 / 2700
Dimensions (H x L x D)	mm	750 x 850 x 298		800 x 850 x 298
Net weight	kg	50		52
Compressor	-		Rotary	
Refrigeration characteristics				
Diameter of pipes (Liq / Gas)	inches	1/4" / 1/2"		1/4" / 5/8"
nitial refrigerant charge	kg	1.5		1.6
Pre-charged for	m	30		
Min. length	m	3		
Max. length / Additional charge	m/g/m	30 / -		
Max. level difference (outdoor unit above / outdoor unit below)	m	20 / 20		
Refrigerant	-		R32	
Electrical features				
Power supply	V/Ph/Hz	230V / 1Ph / 50Hz		
Operating current (Cooling / Heating)	A	5.98-6.52 / 6.31-6.89	7.20-7.85 / 7.74-8.45	8.42-9.18 / 8.84-9.64
sperating carrette (cooting) ricating)	A	3.30=0.32 / 0.31=0.03	,	
Recommended fuse size	A	20	20	20
				20

Controls and compatible accessories (see page 161)



Infrared remote control SPX-RCKA2



Wired standard remote control SPX-RCDB1



Wired programmable remote control SPX-WKT4



H-Link box

PSC-6RAD

Other (price excluding taxes):

- Control box for multi-indoor units SPX-DST1 + SPX-WDST8M
- airCloud Home SPX-WFG02 interface
- Hi-Box AHP-SMB-01
- Hi Kumo gateway for Hi-Box SPX-TAG01
- Single dry contact kit SPX-WDC3

Data includes defrosting. To find out the data for your project, refer to our technical catalogues.

Sound pressure measurements were made 1 meter from the unit without obstructions (see the technical catalogue).

Data shown is for indication purpose only. It is the installer's responsibility to ensure that these cable widths meet the needs of the facility and current standards.