Console Mono-split



Benefits

Benefits






A unique design designed to fit into any room.



It is designed to be as inconspicuous as possible, and this unit can even be built-in.


The ideal unit for small spaces



Very compact, consoles are particularly suitable for installation in smaller rooms.

Greater thermal comfort

The distribution of warm air to the lower part of the room allows it to quickly reach and maintain the desired temperature.



Shirokuma console







High-performance equipment with a unique design





Extended airflow

With a dynamic airflow, the air can reach every corner of the room. The room is air-conditioned (with heating or cooling air) at the touch of a $\,$ button on the remote control. (Fig. 1)

Flexibility with the Multizone range

The indoor unit of the Shirokuma console is compatible with all multi-split outdoor units . You can also have multiple indoor units installed in different rooms with a single outdoor unit.

Exceptionally highperformance

The console has an energy rating of A+++. Guaranteed energy savings!

Management options


The console comes with an infrared remote control as standard. It is also compatible with the SPX-WKT4 wired remote control with hourly programming.

Flexible installation

Wall or floor-mounted on a pedestal (provided).

Compatible with airCloud

The entire Hitachi residential range is compatible with the airCloud system, which allows you to control equipment from any mobile device acting as a remote control.



Indoor units

Outdoor units



RAF-25RXE RAF-35RXE RAF-50RXE








RAC-25FXE

RAC-50FXE



89

Performance, cooling	Unit	2.5 kW	3.5 kW	5.0 kW
Nominal cooling capacity (min-max)	kW	2.50 (0.90 - 3.10)	3.50 (0.90 - 4.00)	5.00 (0.90 - 5.20)
UK total cooling capacity (UK sensible)	kW	2.50 (2.40)	3.50 (2.97)	5.00 (3.57)
Rated power input Cooling (min-max)	kW	0.54 (0.15 - 1.18)	0.93 (0.15 - 1.38)	1.39 (0.5 - 2.10)
EER	-	4.65	3.75	3.60
Energy class Cooling	-	A+++	A+	+
SEER (average climate)	-	8.50	8.20	6.80
Working range in Cooling	°C		-10°C / +46°C	
Performance, heating				
Nominal heating capcity (min-max)	kW	3.40 (0.90 - 4.40)	4.50 (0.90 - 5.00)	6.00 (0.90 - 8.10)
Heating capacity at -7°C(1)	kW	3.40	4.20	5.50
Rated power input Heating (min-max)	kW	0.26 (0.15 - 1.12)	1.15 (0.15 - 1.35)	1.58 (0.5 - 2.70)
COP	-	4.50	3.90	3.80
Energy class Heating	-	A+	+	A+
SCOP (average climate)	-	4.60 4.30		
Working range in Heating	°C		-20°C / +24°C	
Indoor units	Unit	RAF-25RXE	RAF-35RXE	RAF-50RXE
Sound pressure in Cooling mode (EL / L / M / H) (2)	dB(A)	20 / 26 / 31 / 38	20 / 26 / 31 / 39	22 / 29 / 36 / 43
Sound power in Cooling mode	dB(A)	52	53	57
Airflow in Cooling mode (EL / L / M / H)	m³/h	270 / 390 / 510 / 630	270 / 390 / 510 / 660	300 / 450 / 540 / 700
Dehumidification	l/h	1.4	1.9	2.8
Dimensions (H x L x D)	mm	590 x 750 x 215		
Net weight	kg	15		
Remote control	-	Weekly infrared (included)		
Outdoor units	Unit	RAC-25FXE	RAC-35FXE	RAC-50FXE
Sound pressure in cooling mode (2)	dB(A)	45	47	51
Sound power in Cooling mode	dB(A)	59	61	65
Airflow (Cooling / Heating)	m³/h	1860 / 1620	1920 / 1620	2160 / 2160
Dimensions (H x L x D)	mm	600 x 792 x 299		736 x 800 x 350
Net weight	kg	37 51		51
Compressor	-		Rotary	
Refrigeration characteristics				
Diameter of pipes (Liq / Gas)	inches	1/4" / 3/8"		1/4" / 1/2"
Condensate outlet diameter (ext)	mm		16	
Initial refrigerant charge	kg	0.9	8	1.2
Pre-charged for	m	20)	30
Min. length	m		3	
Max. length / Additional charge	m/g/m	20	/ -	30 / -
Max. level difference (outdoor unit above / outdoor unit below)	m	10/10		
Refrigerant	-		R32	
Electrical features				
Power supply	V/Ph/Hz	230V / 1Ph / 50Hz		
Max. current	А	5	7	12
Recommended fuse size	А	15	5	25
Cable width (EN 60 335-1) (3)	mm²	2 x 1.50 + E		2 x 2.50 + E
Indoor/outdoor connection (shielded)	mm²	3 x 1.50 + E		3 x 2.50 + E

Controls and compatible accessories (see page 161)



Infrared remote control RAR-6NE4 Included



Wired standard remote control SPX-RCDB1



Wired programmable remote control SPX-WKT4



H-Link box PSC-6RAD

Other (price excluding taxes):

- Control box for multi-indoor units SPX-DST1 + SPX-WDST8M
- interface airCloud Home SPX-WFG02
- Hi-Box AHP-SMB-01

- Hi Kumo interface for Hi-Box SPX-TAG01
- Single dry contact kit SPX-WDC3
- Leak sensor SPX-RAFGLS

<sup>Data includes defrosting. To find out the data for your project, refer to our technical catalogues.

Sound pressure measurements were made 1 meter from the unit without obstructions (see the technical catalogue).

Data shown is for indication purpose only. It is the installer's responsibility to ensure that these cable widths meet the needs of the facility and current standards.</sup>