

# LG Residential ERV



# Why use **Residential ERV?**

#### Improve Indoor Air Quality

#### **General Behaviors**

People typically spend 90% or more of their time indoors. During the pandemic, this becomes even longer than usual. Consequently, the indoor air quality is of great importance to occupants' comfort, health, and productivity.




#### **New Sustainable Buildings**

In order to reduce energy consumption, the current approach to build energy efficient building is to increase the airtightness of the building envelope. This inevitably reduces uncontrollable building ventilation through the gaps and cracks in the building fabric. To maintain good indoor air quality, ventilator is often required.



#### **Energy Recovery Ventilator (ERV)**

The heat exchanger in the ERV can recover energy from the outgoing exhaust air and transfer it to the incoming fresh air without mixing them. The recovered energy would have otherwise been wasted via natural ventilation.



#### Indoor Air Quality / Indoor Air Pollution



# Neither Air purification nor ventilation is operated There are many pollution sources within the indoor environment. Indoor pollutants vary significantly depending on building usage, but the most common ones include gases and particular matters. Poor indoor air quality can have impact on the health and wellbeing of the building occupants.

#### Air purification is running Fine dust is removed, but harmful substances and high CO<sub>2</sub> concentration remain.




Both the Air purification and ventilation are operated
Not only harmful dust is removed, but also harmful substances and CO<sub>2</sub> are finally exhausted through the ventilation system.

## What is different about

## **LG Residential ERV?**




### Schematic diagram of LG Residential ERV



## Supply Clean Air

① Remove up to 99,99% of harmful particles on Pre-filter with UV nano



UV nano Technology Applied

It Prevents 99.99 % of Bacteria and Viruses from Growing

#### 2 Antibacterial and Anti-Mold Air Passage

In addition to UV sterilization of the pre-filter, the total heat exchanger and air passage (EPS material part) where air passes through are made out of antibacterial and anti-mold material to suppress the growth of bacteria and mold.




- \* Based on Mold Resistance Level: (ASTM G21-15) 0 = No growth, 1 = Grows less than 10 %, 2 = Grows 10-30 %, 3 = Grows 30-60 %, 4 = Grows more than 60 %
- \* Total heat exchange element mold resistance test: Test '20. 11; Testing Institution: FITI Testing and Research Institute; Test Specification: ASTM G21-15; Test strains: Aspergillus brasliensis, Chaetomium globosum, Penicillium funiculosum, Trichoderma virens, Aureobasidium pulluants; Culture conditions: 28-30°C, 85 %RH or higher, 28 days; Test Result: No growth (grade 0) \* Euro (EPS) antibacterial test: Test date and time '20. 8; Testing Institution: FITI Testing and Research Institute; Test standard: JIS Z 2801: 2010, film adhesion method; Test method: Measure the number of bacteria after stationary culture of the test bacterial solution at (35+/-1)°C, 90 %RH for 24 hours; Test strains: Staphylococcus aureus ATCC 6538P, Escherichia coli ATCC 8739; Test result: Antibacterial activity R 4.6 (Strain 1), R6.2 (Strain 2) \*Euro (EPS) mold resistance test: Test date and time '20. 8; Testing Institution: Biotheca; Test Specification: ASTM G21-15; Test strains: Aspergillus niger ATCC 9642, Chaetomium globosum ATCC 6205, Penicillium pinophilum ATCC 11797, Gliocladium virens ATCC 9645, Aureobasidium pulluants ATCC 15233, Cladosporium Cladosporioides IFO 6348; Culture conditions: 29+/-1 °C, 85 % RH, 4 weeks; Test Result: No growth (0 grade)

<sup>\*</sup> Based on laboratory measurements, actual conditions may vary. \* Experimental results are the results of measuring the initial performance of the product and may vary depending on usage time.

#### 3 Fast air cleaning by integration with other IDU

Indoor air quality can be optimized by interfacing ERV with the air purification kit of the 1-way cassette, using indoor particle concentration to control ventilation rate.




It removes fine dust up to twice as fast. When 1 way cassettes senses fine dust is below "unhealthy", ERV is automatically operated in super high mode to remove indoor fine dust quickly.



\* Air Quality Index Table (LG Standard)

Classification	Good	Moderate	Unhealthy	Poor
PM10 (μg/m³)	0 ~ 54	55~ 154	155 ~ 254	255 ~
PM2.5 (μg/m³)	0 ~ 12	13 ~ 35	36 ~ 55	56 ~
PM1.0 (μg/m³)	0 ~ 12	13 ~ 35	36 ~ 55	56 ~



<sup>\*</sup> The above function is applicable when the ventilation is connected with air conditioner with the air purification kit.

<sup>\*</sup> The concentration of fine dust is the result of an actual measurement at Apartment, Seoul, and may vary depending on the environment.

# 2 Smart Control

#### ① Dual Laser Fine Dust Sensor

Two fine dust sensors monitor the incoming air and the supplied air to the room in real time to ensure that clean air is always supplied.



When the measured dust concentration in the air supplied to the room is higher than the pre-set value, a notification or text message will be sent out for filter replacement.



\* Wi-Fi Modem is

Optional.

#### 2 CO<sub>2</sub> Monitoring

The embedded  $CO_2$  sensor monitors the carbon dioxide concentration in the room in real time and automatically controls the ventilation rate.



It monitor  $CO_2$  concentration in the room. It increases the ventilation rate, when the concentration of carbon dioxide is high, and automatically reduces the ventilation rate. if it is low.

\* CO<sub>2</sub> Sensor is Embedded.



\* Wi-Fi Modem is Optional.

#### 3 Control ERV Anytime, Anywhere



- Indoor CO<sub>2</sub> concentration
- Dust concentration in the supply air
- Dust concentration in outdoor air
- \* To use 3<sup>rd</sup> party wall pad, please contact Sales Engineer

Check and Control the Indoor Air Condition Anytime, Anywhere With the dry contact connected, Modbus protocol is available.

#### **4** Filter Maintenance Alarm

The filter replacement notification and text message are sent when the fine dust concentration is higher than the pre-set point.









# 3 Easy Filter Maintenance

Via the one-touch button, the user can open the access door at the bottom of the unit, pull down the heat exchanger to change the filters. It is easy and simple without the need of any additional tools.




# 4 Quiet Operation



### 5 Energy Saving

#### **1** Night Time Free Cooling

It discharges the hot indoor air during summer and supplies cool outdoor air indoor.



<sup>\*</sup> This function is operated with 'Night Time Free Cooling' on remote controller.

#### ② Delay Operation

When the air conditioner & ERV are turned on at the same time, Delay Operation can reduce unnecessary heating and cooling energy loss by automatic delaying the ERV operation.

#### Operation **Delay operation** Operation starts Operation air conditioner simultaneously. Operation starts with air conditioner. ON Energy consumption Off On Acceptable CO2 level Acceptable CO2 level CO<sub>2</sub> level Operation starts Operation starts -Demand Cooling only-→ Demand Cooling & Ventilation → -Demand Cooling only-→ Demand Cooling & Ventilation →


<sup>\*\*</sup> Energy saving rete can be different depending on weather condition

<sup>\*</sup> This function is operated with 'Delay Operation' in remote controller. (with MULTI V, The delay time can be selected between 1 and 60 minutes.)

<sup>\*\*</sup> Energy saving rete can be differed depending on weather condition.

#### 3 CO<sub>2</sub> Auto Operation


By its nature, LG's ERV recovers energy while ventilation. In addition to that, using  $CO_2$  level to control the fan speed saves energy consumption in comparison with a constant fan speed.



 $<sup>\</sup>ensuremath{^{\star}}$  Energy saving rate can be different depending on weather condition.

#### **4** Seasonal Auto Operation

LG ERV senses outdoor temperature and operates automatically following weather condition.



 $<sup>\</sup>mbox{\ensuremath{^{\star}}}$  This function is operated with 'Auto' mode in the wired remote control.

<sup>\*\*</sup> Energy saving rate can be differed depending on weather condition.

#### LG Residential ERV

## **SPECIFICATION**



Model Name			Residential ERV			
Model Name			LZ-H015GBA6	LZ-H020GBA6		
	Capacity	CMH	150	200		
Basic Performance	Power Supply	Ø, V, Hz	1, 220-240, 50	1, 220-240, 50		
	External Static Pressure	Pa	100 / 7	70 / 50		
	Air Flow	CMH	150 / 150 / 80	200 / 200 / 100		
	Dimension (W x H x D)	mm	640 x 32	20 x 640		
	Net Weight	Kg	2	3		
	Current	А	0.43 / 0.38 / 0.23	0.59 / 0.51 / 0.26		
	Power Input	W	56 / 49 / 26	79 / 71 / 30		
ERV mode	Sound Power Level	dB(A)	53 / 51 / 45	55 / 53 / 46		
Enthal	Sound Pressure Level	dB(A)	28 / 26 / 21	30 / 28 / 22		
	Temperature Exchange Efficiency (Heating) (ErP)	%	85	82		
	Enthalpy Exchange Efficiency (Heating / JIS)	%	79 / 79 / 83	75 / 75 / 81		
	Enthalpy Exchange Efficiency (Cooling / JIS)	%	74 / 74 / 80	68 / 68 / 76		
Dunana Mada	Current	А	0.45 / 0.40 / 0.26	0.60 / 0.52 / 0.29		
Bypass Mode	Power Input	W	63 / 53 / 31	84 / 73 / 35		
Filters	Fine Dust Filter	-	ePM₁ 95	95 % filter		
Hygiene	UV LED	-	Removal efficienc	cy up to 99.99 %		
	Total Heat Exchanger	-	Made with grade 0 mold resistance material			
A' O I' D' I	Fine Dust Sensor	-	Default (Indoor / Outdoor)			
Air Quality Display	CO <sub>2</sub> Sensor -	Included by default				
Add-ons	Wi-Fi Modem	-	Optional (PWFMDD200)			
	Dry Contact	-	Optional (PI	DRYCB510)		
	System	-	Rapid air cleaning can be ach air purification kit of M			
Operation / Maintenance	Filter Replacement Alarm	-	Included by default			

Line-up (CMH)

Model	Image	150	200	250	350	500	800	1000	1500	2000
ERV	0.00			0	0	0	0	0	0	0
	NEW	•	•							



O Exsiting line-up

New residential ERV