


SPECIFICATIONS: MODEL 3762

1. ELECTRICAL
 Switch: Single pole, double throw (SPDT)
 Connection: 1/4" (6.4 mm) quick connect, male
 Rating: 16 AMPS. Resistive, 250 V.
 4 AMPS. Inductive, 250 V.

2. MECHANICAL
 Setpoint: Adjustable
 Range: 2 to 22 PSIG (14 to 152 KPa) on pressure rise or pressure fall
 Operating pressure, max: 75 PSIG (517 KPa)
 Temperature: 32°F. to 160°F. (0°C. to 71°C.)
 Mechanical life: 100,000 cycles
 Pressure media: Air or fluids compatible with 300 series stainless steel and EPDM.
 Pressure Connection: 1/8" n.p.t. - male fitting. Fitting is 303 stainless steel, TIG welded to 304 stainless steel mounting pan. Pan/fitting assembly is electroless nickel plated.

This model does not have UL or CSA component recognition.

① The electrical switch component used does carry the following approvals; ENEC (by KEMA), CSA, UL and AGA all of which were separately tested by these agencies to the manufacturers rating indicated.

					DO NOT SCALE DRAWING	UNLESS OTHERWISE SPECIFIED	CONFIDENTIAL AND PROPRIETARY			
					MATERIAL:	1) DIMENSIONS ARE IN INCHES/MILLIMETERS. 2) DIMENSIONS ARE NOMINAL AND ARE FOR REFERENCE ONLY.	THIS PRINT IS THE EXCLUSIVE PROPERTY OF TECMARK CORPORATION AND CANNOT BE REPRODUCED IN WHOLE OR IN PART OR ISSUED OR DISCLOSED TO THIRD PARTIES WITHOUT THE EXPRESSED WRITTEN CONSENT OF TECMARK CORPORATION.			
					FINISH:					
D	14171	EUROPEAN AGENCY WAS "VDE"	11/18/03	GMH			 7745 METRIC DRIVE MENTOR, OHIO NAME: 3000 SERIES SPECIFICATION SHEET			
C	12386	CORRECTED TEMPERATURE SPEC	08/07/98	JFM						
B	12190	ADDED SNAPSWITCH APPROVAL NOTE	06/01/98	R.S.H.			APPROVED BY: <i>ASL</i>			
A	12026	RELEASE TO SALES	04/27/98	R.S.H.			DATE: 11/21/03			
LET.	EN #	DESCRIPTION	DATE	BY	MAKE FROM:	SUPERSEDES:	E.R. NUMBER: 3762	DRAWN BY: R.S.H.	CHECKED BY:	PART NUMBER: BS-3762
						SCALE: NTS	DATE: 04/27/98	DATE:	DATE:	

