Life Is On

eliwell™

by Schneider Electric



D Controls

Adjustable temperature and pressure controls

High-quality & great reliability thanks to Eliwell's application knowledge combined with 30-year expertise in marketing Ranco products

www.eliwell.com

Download My Eliwell APP!

It is the solution to find in real time any information on hundreds of Eliwell products for refrigeration and HVAC systems.

D Controls

Adjustable temperature and pressure controls

D16T - Temperature

SENSING ELEMENT	TEMPERATURE RANGES	-20...+15 °C -4...+59 °F	-10...+25 °C +14...+77 °F	-40...-5 °C -40...+23 °F	+5...+40 °C +41...+104 °F
STRAIGHT CAPILLARY		R automatic D adjustable L 2-3-6-12 m	R automatic D adjustable L 2-3 m	R automatic D adjustable L 2 m	—
		R automatic D fixed L 2-3-6-12 m			
		R manual D fixed L 2-3-6-12 m			
COILED END		R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	—
		R manual D fixed L 2 m			
BULB		R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	—	R automatic D adjustable L 2 m
AMBIENT (CAGE)		R automatic D adjustable	R automatic D adjustable	—	R automatic D adjustable
		R manual D fixed	R manual D fixed		

R = Reset D = Differential L = Sensing element lenght

D16P - Single pressure

FITTING	PRESSURE RANGES	LP -0,3...7 bar -0,4...100 psi	HP 7...31 bar 100...450 psi	HP 10...45 bar 145...650 psi	FAN 7...20 bar 100...290 psi
7\16-20 MALE		R automatic D adjustable	R automatic D adjustable	R automatic D adjustable	R automatic D adjustable
		R manual D fixed	R manual D fixed	R manual D fixed	
CAPILL. 1m with flare 7\16		R automatic D adjustable	R automatic D adjustable	—	R automatic D adjustable
		R manual D fixed	R manual D fixed		

R = Reset D = Differential

D17P - Dual pressure

FITTING	PRESSURE RANGES	LP -0,3...7 bar LP -0,4...100 psi	HP 7...31 bar HP 100...450 psi	LP -0,3...7 bar LP -0,4...100 psi	HP 10...45 bar HP 145...650 psi
7\16-20 MALE		R automatic D adjustable	R automatic D fixed	R automatic D adjustable	R automatic D fixed
		R automatic D adjustable	R manual D fixed		
		R manual D fixed	R manual D fixed	R manual D fixed	R manual D fixed
CAPILL. 1m with flare 7\16		R automatic D adjustable	R automatic D fixed	—	
		R automatic D adjustable	R manual D fixed		
		R manual D fixed	R manual D fixed		

R = Reset D = Differential

Available accessories

Capillary with fittings	Flat and angle bracket	Temperature capillary clip	Top cover	Knob
				

CT123407 • TDS D CONTROLS • EN • rel.12/18 • © Eliwell Controls s.r.l. 2018 - All rights reserved

ITALY - Headquarters

Eliwell Controls srl
Via dell'Industria, 15 Z.I. Paludi
32016 Alpago (BL) - ITALY
T: +39 0437 986 111
F: +39 0437 989 066

Follow us on

Sales
T: +39 0437 986 100 (Italy)
T: +39 0437 986 200 (other countries)
E: saleseliwell@schneider-electric.com

Technical support
T: +39 0437 986 300
E: techsuppeliwell@schneider-electric.com

www.eliwell.com

Download My Eliwell APP!

It is the solution to find in real time any information on hundreds of Eliwell products for refrigeration and HVAC systems.