

# CEILING MOUNTED CASSETTE (4 WAY)



LG participates in the ECP programme for EUROVENT VRF program. Check ongoing validity of certification : [www.eurovent-certification.com](http://www.eurovent-certification.com)

## 4 Way Cassette

INDOOR				MT06R NRO	MT08R NRO
Capacity	Cooling / Heating	Nom.	kW	1.5 / 1.6	2.1 / 2.3
Power Input		Nom.	W	20	20
Running Current		Nom.	A	0.40	0.40
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate		H / M / L	m <sup>3</sup> /min	7.5 / 6.0 / 5.0	7.5 / 6.0 / 5.0
Sound Pressure	Cooling	H / M / L	dB(A)	31 / 27 / 24	31 / 27 / 24
Sound Power	Cooling	Max.	dB(A)	48	48
Dehumidification Rate			l/h	-	-
Dimensions	Body	W x H x D	mm	570 x 214 x 570	570 x 214 x 570
Net Weight	Body		kg	11.7	11.7
Piping Connection	Liquid		mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)
Decoration Panel	Model			PT-QCHW0	PT-QCHW0
	Color			Morning Fog (9001)	Morning Fog (9001)
	Dimensions	W x H x D	mm	620 x 34 x 620	620 x 34 x 620
	Weight		kg	3	3

INDOOR				CT09F NRO	CT12F NRO	CT18F NQ0	CT24F NBO
Capacity	Cooling / Heating	Nom.	kW	2.6 / 2.9	3.5 / 3.9	5.3 / 5.8	6.7 / 7.5
Power Input		Nom.	W	22	24	26	26
Running Current		Nom.	A	0.40	0.40	0.40	0.60
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Air Flow Rate		H / M / L	m <sup>3</sup> /min	8.5 / 7.0 / 6.0	9.5 / 8.0 / 7.0	13.0 / 12.0 / 11.0	17.0 / 15.0 / 13.0
Sound Pressure	Cooling	H / M / L	dB(A)	36 / 33 / 30	38 / 35 / 32	41 / 39 / 39	38 / 36 / 34
Sound Power	Cooling	Max.	dB(A)	52	52	57	53
Dehumidification Rate			l/h	0.9	1.4	2.0	2.7
Dimensions	Body	W x H x D	mm	570 x 214 x 570	570 x 214 x 570	570 x 256 x 570	840 x 204 x 840
Net Weight	Body		kg	12.4	12.4	13.9	21.1
Piping Connection	Liquid		mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø12.7 (1/2)	Ø12.7 (1/2)
Decoration Panel	Model			PT-QAGW0	PT-QAGW0	PT-QAGW0	PT-AAGW0
	Color			White (9003)	White (9003)	White (9003)	White (9003)
	Dimensions	W x H x D	mm	620 x 35 x 620	620 x 35 x 620	620 x 35 x 620	950 x 35 x 950
	Weight		kg	2.9	2.9	2.9	7.1

☐ Dual vane is applied to 24k

☐ This product contains Fluorinated greenhouse gases (R32).

☐ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.