

MECHANICAL DATA

Displacement:	197.1 cm ³ /rev (34.3 m ³ /h)
Maximum Recommended Refrigerant Charge:	10.5 ml
Weight:	54 kg

At maximum evaporating temperature and maximum ambient temperature.

ELECTRICAL DATA

Motor Type:	Induction motor -
Pole:	2 -
Starting Torque:	HST -
Voltage Working Range 50Hz:	342-462 V
Voltage Working Range 60Hz:	414-506 V
Maximum Motor Temperature:	130 °C
Motor Insulation Class:	B -
Run Winding Resistance:	1.06 Ω (± 10%) at 25°C
Start Winding Resistance:	- Ω (± 10%) at 25°C

At maximum evaporating temperature and maximum ambient temperature.

ELECTRICAL COMPONENTS

	Component type	Description	Code
Motor Protection:	Internal protector	-	-
Starting Device:	-	-	-
Start Capacitor:	-	-	-
Run Capacitor:	-	-	-
CSR Box:	-	-	-

ACCESSORIES

	Includes
Cover:	yes
Cover Gasket:	yes
Grounding Screw:	yes
Liquid Injection:	-
Temperature Sensor:	-
Grommets:	yes
Sleeves:	yes
Crankcase Heater:	90
Noise Insulation:	-
Rotolock Valves:	-
Rotolock Adapter:	-
Service Valves:	-

For additional accessories please contact our technical support

EXTERNAL CHARACTERISTICS

Base Plate Max Dimensions:	232x232mm
Base Plate Holes Interaxis:	191x191mm
Height:	506mm
Compressor Shell Diameter:	197mm
Hanger Tab:	yes
Oil Side Glass:	yes

	Shape	Material	Internal Diameter (mm)
Suction Connector	Brazing	Copper plated steel tube	ID 28.83 mm
Discharge Connector	Brazing	Copper plated steel tube	ID 22.47 mm

RATED POINTS

Conditions	380V 50Hz	460V 60Hz	380V 50Hz	460V 60Hz
	EN12900: Te -10°C; Tc 45°C; Rg 20°C; No subcooling; Ta 35°C	EN12900: Te -10°C; Tc 45°C; Rg 20°C; No subcooling; Ta 35°C	ARI540(2004): Te -6.7°C; Tc 48.9°C; Rg 4.4°C; No subcooling; Ta 35°C	ARI540(2004): Te -6.7°C; Tc 48.9°C; Rg 4.4°C; No subcooling; Ta 35°C
Capacity (W)	20585	24702	20544	24653
Power Input (W)	9255	11106	10170	12204
COP (W/W)	2.22	2.22	2.02	2.02
Rated Load Amps RLA (A)	15.8	15.8	16.9	16.9
Locked Rotor Amps LRA (A)	121	121	121	121
Maximum Operating Current MOC (A)	27.6	27.6	27.6	27.6
Sound Power Level (dBA)	77	79	77	79

PERFORMANCE CURVE DATA

Standard: EN 12900 / w

50 Hz

	Evaporating Temperature (°C)	Cooling Capacity (w)	Power Consumption (W)	Efficiency (w/W)
35°C Condensing Temperature	10°C	46 726	8 976	5.21
	5°C	39 348	8 566	4.59
	0°C	33 103	8 231	4.02
	-5°C	27 825	7 946	3.50
	-10°C	23 345	7 689	3.04
	-15°C	19 497	7 437	2.62
	-20°C	16 112	7 165	2.25
	-25°C	13 024	6 852	1.90
	-30°C	10 065	6 473	1.56
45°C Condensing Temperature	10°C	39 154	10 247	3.82
	5°C	33 411	9 863	3.39
	0°C	28 503	9 544	2.99
	-5°C	24 264	9 266	2.62
	-10°C	20 527	9 006	2.28
	-15°C	17 123	8 740	1.96
	-20°C	13 885	8 446	1.64
	-25°C	10 646	8 100	1.31
	-30°C	7 238	7 679	0.94

	Evaporating Temperature (°C)	Cooling Capacity (w)	Power Consumption (W)	Efficiency (w/W)
55°C Condensing Temperature	10°C	31 308	12 280	2.55
	5°C	26 933	11 959	2.25
	0°C	23 096	11 692	1.98
	-5°C	19 630	11 457	1.71
	-10°C	16 367	11 230	1.46
	-15°C	13 141	10 988	1.20
	-20°C	9 783	10 708	0.91
	-25°C	6 126	10 366	0.59