

PACi NX Series Elite wall-mounted - PK3 · R32

For light refrigeration applications.



nanoe™ X as a standard.



| | | | | High temperature | | | | | | | |
|--------------------------|--------------------------|-------------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Kit | | | | 36 | 50 | 60 | 71 | 100 | 125 | 140 | |
| Indoor unit - 1 | | | | S-6010PK3E | S-6010PK3E | S-6010PK3E | S-6010PK3Ex2 | S-6010PK3E | S-6010PK3E | S-6010PK3E | |
| Indoor unit - 2 | | | | | | | | S-6010PK3E | S-6010PK3E | S-6010PK3E | |
| Outdoor unit | | | | U-36PZH3E5 | U-50PZH3E5 | U-60PZH3E5 | U-71PZH4E5/8 | U-100PZH4E5/8 | U-125PZH4E5/8 | U-140PZH4E5/8 | |
| Outdoor 35 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,50 | 4,90 | 5,80 | 6,90 | 8,80 | 11,60 | 13,00 | |
| | | EER | | 4,55 | 3,83 | 3,56 | 3,17 | 2,97 | 3,06 | 3,34 | |
| | | Input power | kW | 0,77 | 1,28 | 1,63 | 2,18 | 2,96 | 3,79 | 3,89 | |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,19 | 4,46 | 5,28 | 6,28 | 8,01 | 10,56 | 11,83 | |
| | | EER | | 4,22 | 3,55 | 3,30 | 2,94 | 2,76 | 2,84 | 3,10 | |
| | | Input power | kW | 0,75 | 1,25 | 1,60 | 2,14 | 2,90 | 3,71 | 3,81 | |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,27 | 4,14 | 5,28 | 6,96 | 7,80 | |
| | | EER | | 3,50 | 2,94 | 2,14 | 2,44 | 2,28 | 2,35 | 2,57 | |
| | | Input power | kW | 0,60 | 1,00 | 1,52 | 1,70 | 2,31 | 2,96 | 3,03 | |
| | Outdoor 30 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,75 | 5,24 | 5,92 | 7,04 | 9,42 | 12,41 | 13,91 |
| | | | EER | | 5,29 | 4,45 | 3,86 | 3,44 | 3,45 | 3,56 | 3,88 |
| | | | Input power | kW | 0,71 | 1,18 | 1,53 | 2,05 | 2,72 | 3,49 | 3,58 |
| Indoor 12 °C (WB) | | Cooling capacity | kW | 3,43 | 4,80 | 5,39 | 6,42 | 8,62 | 11,37 | 12,74 | |
| | | EER | | 4,95 | 4,17 | 3,60 | 3,20 | 3,23 | 3,33 | 3,64 | |
| | | Input power | kW | 0,69 | 1,15 | 1,50 | 2,01 | 2,66 | 3,41 | 3,50 | |
| Indoor 8 °C (WB) | | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 4,14 | 5,28 | 6,96 | 7,80 | |
| | | EER | | 3,90 | 3,28 | 2,97 | 2,64 | 2,55 | 2,62 | 2,86 | |
| | | Input power | kW | 0,54 | 0,90 | 1,17 | 1,57 | 2,16 | 2,65 | 2,72 | |
| Indoor unit | | Dimension (HxWxD) | mm | 302 x 1120 x 236 | 302 x 1120 x 236 | 302 x 1120 x 236 | 302 x 1120 x 236 | 302 x 1120 x 236 | 302 x 1120 x 236 | 302 x 1120 x 236 | 302 x 1120 x 236 |
| | | Net weight | kg | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 |
| | | nanoe X Generator | | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 |
| Outdoor unit | Dimension (HxWxD) | mm | 695 x 875 x 320 | 695 x 875 x 320 | 695 x 875 x 320 | 996 x 980 x 370 | 996 x 980 x 370 | 996 x 980 x 370 | 996 x 980 x 370 | 996 x 980 x 370 | |
| | Net weight | kg | 42 | 42 | 43 | 66 | 84 | 86 | 86 | | |

Accessories

| | |
|----------------------------------|--|
| CZ-RTC6W ¹⁾ | CONEX wired remote controller (non-wireless), white |
| CZ-RTC6WBL ¹⁾ | CONEX wired remote controller with Bluetooth®, white |
| CZ-RTC6WBLW ¹⁾ | CONEX wired remote controller with Wi-Fi and Bluetooth®, white |
| CZ-RTC6 | CONEX wired remote controller (non-wireless), black |
| CZ-RTC6BL | CONEX wired remote controller with Bluetooth®, black |
| CZ-RTC6BLW | CONEX wired remote controller with Wi-Fi and Bluetooth®, black |
| CZ-RTC5B | Wired remote controller with Econavi function and datanavi |
| CZ-RWS3 | Infrared remote controller |

1) Available in Autumn 2023.

Accessories

| | |
|---------------------|---|
| PAW-PACR4 | Interface to run up to 4 indoor unit groups on backup and alternative run |
| PAW-WTRAY | Tray for condenser water compatible with outdoor elevation platform |
| PAW-GRDBSE20 | Outdoor base ground support for noise and vibration absorption |
| PAW-GRDSTD40 | Outdoor elevation platform 400 x 900 x 400 mm |
| CZ-CENSC1 | Econavi energy saving sensor |

Technical focus

- Modern design with flat face and compact size
- DC fan for better efficiency and control
- Six directional piping outlet
- nanoe™ X (Generator Mark 2= 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit

Closed discharge port

When the unit is turned OFF, the flap closes completely to prevent dust getting into the unit and to keep the equipment clean.

Quiet operation

These units are among the quietest in the industry, making them ideal for all types of installations.

Piping outlet in six directions

Piping outlet is possible in six directions of; right, right rear, right bottom, left, left rear and left bottom, making the installation work more flexible.

PACi NX Series Elite 4 way 90x90 cassette - PU3 · R32

For light refrigeration applications.



nanoe™ X as a standard.



| Kit | | | High temperature | | | | | | | | | | |
|--------------------------|-------------------------|------------------|-------------------|------------|-------------|--------------|---------------|---------------|---------------|-------------|-------------|--------------|--------------|
| | | | 36 | 50 | 60 | 71 | 100 | 125 | 140 | 200 | 250 | | |
| Indoor unit - 1 | | | S-6071PU3E | S-6071PU3E | S-6071PU3E | S-1014PU3E | S-1014PU3E | S-1014PU3E | S-1014PU3E | S-1014PU3E | S-1014PU3E | | |
| Indoor unit - 2 | | | — | — | — | — | — | — | S-1014PU3E | S-1014PU3E | S-1014PU3E | | |
| Outdoor unit | | | U-36PZH3E5 | U-50PZH3E5 | U-60PZH3E5 | U-71PZH4E5/8 | U-100PZH4E5/8 | U-125PZH4E5/8 | U-140PZH4E5/8 | U-200PZH2E8 | U-250PZH2E8 | | |
| Outdoor 35 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,50 | 4,90 | 5,80 | 6,90 | 8,80 | 11,60 | 13,00 | 18,50 | 23,20 | |
| | | EER | | 5,12 | 4,05 | 3,81 | 3,67 | 4,09 | 3,47 | 3,82 | 3,38 | 2,97 | |
| | | Input power | kW | 0,68 | 1,21 | 1,52 | 1,88 | 2,15 | 3,34 | 3,40 | 5,48 | 7,82 | |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,19 | 4,46 | 5,28 | 6,28 | 8,01 | 10,56 | 11,83 | 16,84 | 21,11 | |
| | | EER | | 4,78 | 3,76 | 3,54 | 3,41 | 3,80 | 3,22 | 3,55 | 3,13 | 2,75 | |
| | | Input power | kW | 0,67 | 1,19 | 1,49 | 1,84 | 2,11 | 3,27 | 3,33 | 5,37 | 7,66 | |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 4,14 | 5,28 | 6,96 | 7,80 | 11,10 | 13,92 | |
| | | EER | | 3,96 | 3,12 | 2,94 | 2,82 | 3,15 | 2,67 | 2,94 | 2,60 | 2,28 | |
| | | Input power | kW | 0,53 | 0,94 | 1,19 | 1,47 | 1,68 | 2,61 | 2,65 | 4,27 | 6,10 | |
| Outdoor 30 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,75 | 5,24 | 5,92 | 7,04 | 9,42 | 12,41 | 13,91 | 20,17 | 25,29 | |
| | | EER | | 5,99 | 4,71 | 4,14 | 3,98 | 4,76 | 4,04 | 4,45 | 4,00 | 3,51 | |
| | | Input power | kW | 0,63 | 1,11 | 1,43 | 1,77 | 1,98 | 3,07 | 3,13 | 5,04 | 7,19 | |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,43 | 4,80 | 5,39 | 6,42 | 8,62 | 12,41 | 12,74 | 18,50 | 23,20 | |
| | | EER | | 5,60 | 4,41 | 3,86 | 3,71 | 4,46 | 4,04 | 4,16 | 3,75 | 3,30 | |
| | | Input power | kW | 0,61 | 1,09 | 1,40 | 1,73 | 1,94 | 3,07 | 3,06 | 4,93 | 7,04 | |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 4,14 | 5,28 | 6,96 | 7,80 | 11,10 | 13,92 | |
| | | EER | | 4,41 | 3,47 | 3,18 | 3,06 | 3,51 | 2,98 | 3,28 | 2,89 | 2,54 | |
| | | Input power | kW | 0,48 | 0,85 | 1,09 | 1,35 | 1,51 | 2,34 | 2,38 | 3,84 | 5,47 | |
| Indoor unit | | | Dimension (HxWxD) | mm | 256x840x840 | 256x840x840 | 256x840x840 | 319x840x840 | 319x840x840 | 319x840x840 | 319x840x840 | 319x840x840 | |
| | | | Net weight | kg | 19 | 19 | 20 | 25 | 25 | 25 | 25 | 25 | |
| | | | nanoe X Generator | | Mark 1 | Mark 1 | Mark 1 | Mark 1 | Mark 1 | Mark 1 | Mark 1 | Mark 1 | |
| Outdoor unit | | | Dimension (HxWxD) | mm | 695x875x320 | 695x875x320 | 695x875x320 | 996x980x370 | 996x980x370 | 996x980x370 | 996x980x370 | 1500x980x370 | 1500x980x370 |
| | | | Net weight | kg | 42 | 42 | 43 | 66 | 84 | 86 | 86 | 117 | 128 |

Accessories

| | |
|----------------------------------|--|
| CZ-RTC6W ¹⁾ | CONEX wired remote controller (non-wireless), white |
| CZ-RTC6WBL ¹⁾ | CONEX wired remote controller with Bluetooth®, white |
| CZ-RTC6WBLW ¹⁾ | CONEX wired remote controller with Wi-Fi and Bluetooth®, white |
| CZ-RTC6 | CONEX wired remote controller (non-wireless), black |
| CZ-RTC6BL | CONEX wired remote controller with Bluetooth®, black |
| CZ-RTC6BLW | CONEX wired remote controller with Wi-Fi and Bluetooth®, black |
| CZ-RTC5B | Wired remote controller with Econavi function and datanavi |

Accessories

| | |
|----------------------------|---|
| CZ-RWS3 + CZ-RWRU3W | Infrared remote controller and receiver |
| CZ-KPU3AW | Econavi exclusive panel |
| PAW-WTRAY | Tray for condenser water compatible with outdoor elevation platform |
| PAW-GRDBSE20 | Outdoor base ground support for noise and vibration absorption |
| PAW-GRDSTD40 | Outdoor elevation platform 400x900x400 mm |
| CZ-FDU3+CZ-ATU2 | Fresh air-intake kit |

1) Available in Autumn 2023.

Technical focus

- High performance turbo fan
- Econavi: An optional intelligent sensor to reduce waste of energy
- nanoe™ X (Generator Mark 1= 4,8 trillion hydroxyl radicals/sec) as standard for better indoor air quality, indoor unit internal cleaning with nanoe™ X plus dry operation
- Lower noise in low fan operation
- Light weight, easy piping and integrated drain pump for quick installation
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- High volume fresh air input with optional air-intake plenum and chamber (CZ-FDU3+CZ-ATU2)

PACi NX Series Elite ceiling - PT3 · R32

For light refrigeration applications.



nanoex™ X as a standard.



| | | High temperature | | | | | | | | | | |
|--------------------------|-------------------------|------------------|--------------|--------------|--------------|---------------|---------------|---------------|--------------|--------------|--------------|-------|
| Kit | | 36 | 50 | 60 | 71 | 100 | 125 | 140 | 200 | 250 | | |
| Indoor unit - 1 | | S-6071PT3E | S-6071PT3E | S-1014PT3E | S-1014PT3E | S-1014PT3E | S-1014PT3E | S-1014PT3E | S-1014PT3E | S-1014PT3E | | |
| Indoor unit - 2 | | — | — | — | — | — | — | S-1014PT3E | S-1014PT3E | S-1014PT3E | | |
| Outdoor unit | | U-36PZH3E5 | U-50PZH3E5 | U-60PZH3E5 | U-71PZH4E5/8 | U-100PZH4E5/8 | U-125PZH4E5/8 | U-140PZH3E5/8 | U-200PZH2E8 | U-250PZH2E8 | | |
| Outdoor 35 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,50 | 4,90 | 5,80 | 6,60 | 8,80 | 11,20 | 13,00 | 18,50 | 23,20 |
| | | EER | | 4,67 | 3,71 | 3,63 | 3,53 | 3,76 | 3,15 | 3,40 | 3,32 | 2,92 |
| | | Input power | kW | 0,75 | 1,32 | 1,60 | 1,87 | 2,34 | 3,56 | 3,82 | 5,57 | 7,94 |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,19 | 4,46 | 5,28 | 6,01 | 8,01 | 10,19 | 11,83 | 16,84 | 21,11 |
| | | EER | | 4,33 | 3,45 | 3,37 | 3,28 | 3,49 | 2,92 | 3,16 | 3,08 | 2,71 |
| | | Input power | kW | 0,74 | 1,29 | 1,57 | 1,83 | 2,29 | 3,49 | 3,74 | 5,46 | 7,78 |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 3,96 | 5,28 | 6,72 | 7,80 | 11,10 | 13,92 |
| | | EER | | 3,59 | 2,86 | 2,79 | 2,71 | 2,89 | 2,42 | 2,62 | 2,55 | 2,25 |
| | | Input power | kW | 0,59 | 1,03 | 1,25 | 1,46 | 1,83 | 2,78 | 2,98 | 4,34 | 6,19 |
| Outdoor 30 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,75 | 5,24 | 5,92 | 6,73 | 9,42 | 11,98 | 13,91 | 20,17 | 25,29 |
| | | EER | | 5,43 | 4,32 | 3,93 | 3,83 | 4,37 | 3,66 | 3,96 | 3,94 | 3,46 |
| | | Input power | kW | 0,69 | 1,21 | 1,50 | 1,76 | 2,15 | 3,28 | 3,51 | 5,12 | 7,30 |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,43 | 4,80 | 5,39 | 6,14 | 8,62 | 10,98 | 12,74 | 18,50 | 23,20 |
| | | EER | | 5,08 | 4,04 | 3,66 | 3,57 | 4,09 | 3,43 | 3,71 | 3,69 | 3,25 |
| | | Input power | kW | 0,68 | 1,19 | 1,47 | 1,72 | 2,11 | 3,20 | 3,44 | 5,01 | 7,15 |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 3,96 | 5,28 | 6,72 | 7,80 | 11,10 | 13,92 |
| | | EER | | 4,00 | 3,18 | 3,02 | 2,94 | 3,22 | 2,70 | 2,92 | 2,85 | 2,50 |
| | | Input power | kW | 0,53 | 0,92 | 1,15 | 1,35 | 1,64 | 2,49 | 2,67 | 3,90 | 5,56 |
| Indoor unit | Dimension (HxWxD) | mm | 235x1275x690 | 235x1275x690 | 235x1590x690 | 235x1590x690 | 235x1590x690 | 235x1590x690 | 235x1590x690 | 235x1590x690 | 235x1590x690 | |
| | Net weight | kg | 34 | 34 | 40 | 40 | 40 | 40 | 40 | 40 | 40 | |
| | nanoex X Generator | | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | |
| Outdoor unit | Dimension (HxWxD) | mm | 695x875x320 | 695x875x320 | 695x875x320 | 996x980x370 | 996x980x370 | 996x980x370 | 996x980x370 | 1500x980x370 | 1500x980x370 | |
| | Net weight | kg | 42 | 42 | 43 | 66 | 84 | 86 | 86 | 117 | 128 | |

Accessories

| | |
|----------------------------------|--|
| CZ-RTC6W ¹⁾ | CONEX wired remote controller (non-wireless), white |
| CZ-RTC6WBL ¹⁾ | CONEX wired remote controller with Bluetooth®, white |
| CZ-RTC6WBLW ¹⁾ | CONEX wired remote controller with Wi-Fi and Bluetooth®, white |
| CZ-RTC6 | CONEX wired remote controller (non-wireless), black |
| CZ-RTC6BL | CONEX wired remote controller with Bluetooth®, black |
| CZ-RTC6BLW | CONEX wired remote controller with Wi-Fi and Bluetooth®, black |
| CZ-RTC5B | Wired remote controller with Econavi function and datanavi |

1) Available in Autumn 2023.

Accessories

| | |
|---------------------------|---|
| CZ-RWS3 + CZ-RWRT3 | Infrared remote controller and receiver |
| PAW-WTRAY | Tray for condenser water compatible with outdoor elevation platform |
| PAW-GRDBSE20 | Outdoor base ground support for noise and vibration absorption |
| PAW-GRDSTD40 | Outdoor elevation platform 400x900x400 mm |
| CZ-CENSC1 | Econavi energy saving sensor |

Technical focus

- Wide air distribution for large rooms
- Horizontal air flow reaches maximum 9,5 m
- Fresh air connection available on the unit
- Slim design with 235 mm height fits narrow space
- Silent operation
- nanoex™ X (Generator Mark 2= 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- Twin, Triple and Double-twin split options
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit

Further comfort improvement with airflow distribution

Horizontal air flow reaches maximum 9,5 m. This is ideal for wide rooms.

The wide air discharge opening expands the air flow to the left and right. The unpleasant feeling caused when the air flow directly hits the human body is prevented by the "Draft prevention position", which changes the swing width, so that the degree of comfort is increased.

PACi NX Series Elite adaptive ducted unit - PF3 · R32

For light refrigeration applications.

nanoe™ X

nanoe™ X as a standard.



| | | | High temperature | | | | | | | | | |
|--------------------------|-------------------------|------------------|------------------|--------------|--------------|--------------|---------------|---------------|---------------|--------------|--------------|-------|
| Kit | | | 36 | 50 | 60 | 71 | 100 | 125 | 140 | 200 | 250 | |
| Indoor unit - 1 | | | S-6071PF3E | S-6071PF3E | S-6071PF3E | S-1014PF3E | S-1014PF3E | S-1014PF3E | S-1014PF3E | S-1014PF3E | S-1014PF3E | |
| Indoor unit - 2 | | | — | — | — | — | — | — | S-1014PF3E | S-1014PF3E | S-1014PF3E | |
| Outdoor unit | | | U-36PZH3E5 | U-50PZH3E5 | U-60PZH3E5 | U-71PZH4E5/8 | U-100PZH4E5/8 | U-125PZH4E5/8 | U-140PZH4E5/8 | U-200PZH2E8 | U-250PZH2E8 | |
| Outdoor 35 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,50 | 4,90 | 5,80 | 6,60 | 8,80 | 11,20 | 13,00 | 18,50 | 23,20 |
| | | EER | | 3,98 | 3,20 | 3,52 | 3,37 | 3,79 | 3,21 | 3,59 | 3,50 | 3,08 |
| | | Input power | kW | 0,88 | 1,53 | 1,65 | 1,96 | 2,32 | 3,49 | 3,62 | 5,29 | 7,54 |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,19 | 4,46 | 5,28 | 6,01 | 8,01 | 10,19 | 11,83 | 16,84 | 21,11 |
| | | EER | | 3,69 | 2,97 | 3,26 | 3,13 | 3,52 | 2,98 | 3,33 | 3,25 | 2,86 |
| | | Input power | kW | 0,86 | 1,50 | 1,62 | 1,92 | 2,27 | 3,42 | 3,55 | 5,18 | 7,39 |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 3,96 | 5,28 | 6,72 | 7,80 | 11,10 | 13,92 |
| | | EER | | 3,06 | 2,46 | 2,70 | 2,59 | 2,92 | 2,47 | 2,76 | 2,69 | 2,37 |
| | | Input power | kW | 0,69 | 1,19 | 1,29 | 1,53 | 1,81 | 2,72 | 2,82 | 4,13 | 5,88 |
| Outdoor 30 °C (DB) | Indoor 15 °C (WB) | Cooling capacity | kW | 3,75 | 5,24 | 5,92 | 6,73 | 9,42 | 11,98 | 13,91 | 20,17 | 25,29 |
| | | EER | | 4,63 | 3,72 | 3,81 | 3,65 | 4,41 | 3,73 | 4,18 | 4,14 | 3,65 |
| | | Input power | kW | 0,81 | 1,41 | 1,55 | 1,84 | 2,13 | 3,21 | 3,33 | 4,87 | 6,94 |
| | Indoor 12 °C (WB) | Cooling capacity | kW | 3,43 | 4,80 | 5,39 | 6,14 | 8,62 | 10,98 | 12,74 | 18,50 | 23,20 |
| | | EER | | 4,33 | 3,49 | 3,55 | 3,40 | 4,13 | 3,49 | 3,91 | 3,89 | 3,42 |
| | | Input power | kW | 0,79 | 1,38 | 1,52 | 1,80 | 2,09 | 3,14 | 3,26 | 4,76 | 6,79 |
| | Indoor 8 °C (WB) | Cooling capacity | kW | 2,10 | 2,94 | 3,48 | 3,96 | 5,28 | 6,72 | 7,80 | 11,10 | 13,92 |
| | | EER | | 3,41 | 2,75 | 2,93 | 2,81 | 3,25 | 2,75 | 3,08 | 3,00 | 2,64 |
| | | Input power | kW | 0,62 | 1,07 | 1,19 | 1,41 | 1,62 | 2,44 | 2,53 | 3,70 | 5,28 |
| Indoor unit | Dimension (HxWxD) | mm | 250x1000x730 | 250x1000x730 | 250x1000x730 | 250x1400x730 | 250x1400x730 | 250x1400x730 | 250x1400x730 | 250x1400x730 | 250x1400x730 | |
| | Net weight | kg | 30 | 30 | 30 | 39 | 39 | 39 | 39 | 39 | 39 | |
| | nanoe X Generator | | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | Mark 2 | |
| Outdoor unit | Dimension (HxWxD) | mm | 695x875x320 | 695x875x320 | 695x875x320 | 996x980x370 | 996x980x370 | 996x980x370 | 996x980x370 | 1500x980x370 | 1500x980x370 | |
| | Net weight | kg | 42 | 42 | 43 | 66 | 84 | 86 | 84 | 117 | 128 | |

Accessories

| | |
|----------------------------------|--|
| CZ-RTC6W ¹⁾ | CONEX wired remote controller (non-wireless), white |
| CZ-RTC6WBL ¹⁾ | CONEX wired remote controller with Bluetooth®, white |
| CZ-RTC6WBLW ¹⁾ | CONEX wired remote controller with Wi-Fi and Bluetooth®, white |
| CZ-RTC6 | CONEX wired remote controller (non-wireless), black |
| CZ-RTC6BL | CONEX wired remote controller with Bluetooth®, black |
| CZ-RTC6BLW | CONEX wired remote controller with Wi-Fi and Bluetooth®, black |
| CZ-RTC5B | Wired remote controller with Econavi function and datanavi |
| CZ-RWS3 + CZ-RWRC3 | Infrared remote controller and receiver |

1) Available in Autumn 2023.

Technical focus

- 2 installation possibilities (horizontal / vertical)
- Maximum external static pressure: 150 Pa
- Selectable inlet air position (rear / bottom entry)
- Improved drain pan suitable for both horizontal / vertical installation
- Drain pump included
- nanoe™ X (Generator Mark 2= 9,6 trillion hydroxyl radicals/sec) as standard for the long duct piping case*
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®

* The performance of nanoe™ X air can be expected even by 10 m long duct by Panasonic internal survey.

Accessories

| | |
|---------------------|---|
| PAW-WTRAY | Tray for condenser water compatible with outdoor elevation platform |
| PAW-GRDBSE20 | Outdoor base ground support for noise and vibration absorption |
| PAW-GRDSTD40 | Outdoor elevation platform 400x900x400 mm |
| CZ-CENSC1 | Econavi energy saving sensor |
| CZ-56DAF2 | Air outlet plenum for S-3650PF3E |
| CZ-90DAF2 | Air outlet plenum for S-6071PF3E |
| CZ-160DAF2 | Air outlet plenum for S-1014PF3E |

2 installation possibilities (horizontal / vertical)

Vertical installation is available. ESP 150Pa, sufficient for remotely installing units away from the rooms.



Improved drain pan design

Drain pan is shared in both cases horizontal and vertical installation. No need to modify the unit.

